

MATERIAL HANDLING HOSE

4313

LIGHTWEIGHT SANDBLAST HOSE



CONSTRUCTION: Tube is SBR/NR blend which is static dissipating. Cover is an SBR/NR blend, black. Reinforcement is a two-ply synthetic fabric.

TEMPERATURE: -25°F (-32°C) to +185°F (+85°C)

BRANDING: Jason logo 4313 LW SANDBLAST 1-7/8" O.D.
WP 150 PSI 10.35 BAR.
White longitudinal mylar stripe.

APPLICATION: For conveyance of highly abrasive materials in sandblasting/cleaning operations.

SAFETY FACTOR: 3:1

FEATURES:

- Tube compounds are static-dissipating
- Highly abrasion resistant tube that will handle any blast grit
- Cover is abrasion and weather resistant
- Lighter weight than standard sandblast hose
- Maintains the high quality features
- Utilizes couplings or nozzle holders made to fit 1-7/8" O.D. hose

Part Number	I.D.		O.D.		Reinf. Plies	Max W.P. @ 68°F		Vacuum @ 68°F	Weight		Minimum Bend Radius		Std. Length (ft.)
	in.	mm	in.	mm		PSI	BAR		lb./ft.	KG/m	in.	mm	
4313-0125-050	1-1/4	31.75	1.88	47.63	2	150	10.35	n/a	0.83	1.24	10.00	254.00	50
4313-0125-100	1-1/4	31.75	1.88	47.63	2	150	10.35	n/a	0.83	1.24	10.00	254.00	100
4313-0125-200	1-1/4	31.75	1.88	47.63	2	150	10.35	n/a	0.83	1.24	10.00	254.00	200

Working pressure (W.P.) is temperature dependent. See the General Information section Table II - Pressure Re-Rating for increased Temperatures (Page 10) for more information.

All sizes may not be stocked in all locations. Check with customer service for availability.
We disclaim any liability for use of our products in applications other than which they are designed.

WARNING: This product can expose you to chemicals including carbon black, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information visit www.P65WARNINGS.ca.gov