PETROLEUM HOSE



4328

NITRILE FUEL DISCHARGE HOSE - 300 PSI - $S\Omega$







CONSTRUCTION: Tube is nitrile, smooth, ARPM

Class A. Cover is CR, black, ARPM Class B. Reinforcement is two-ply synthetic fabric with a static wire.

TEMPERATURE: -25°F (-32°C) to +200°F (+93°C)

BRANDING: Jason logo 4328 FUEL DISCHARGE WP

300 PSI 20.7 BAR.

Red mylar longitudinal stripe.

SAFETY FACTOR: 3:1

APPLICATION: For discharge only. For petroleum-based products in truck and car applications.

FEATURES:

- HD construction that handles up to 300 PSI applications
- Cover is resistant to weathering and abrasion
- Class A tube is highly oil resistant and handles gasoline and other petroleum products having an aromatic content of 50%.
- Safety Ohm (SΩ) ground wire embedded into the hose wall to help prevent the build-up of static electricity.
 SΩ wire must be secured to ground to dissipate static electricity.

Part Number	I.D.		O.D.		Reinf. Plies	Max W.P. @ 68°F		Vacuum @ 68°F	Weight		Minimum Bend Radius		Std. Length
	in.	mm	in.	mm	Files	PSI	BAR	₩ 00 F	lb./ft.	KG/m	in.	mm	(ft.)
4328-0200-100	2	50.80	2.64	67.06	2	300	20.68	n/a	1.35	2.01	11.00	275.00	100
4328-0250-100	2-1/2	63.50	3.13	79.50	2	300	20.68	n/a	1.55	2.30	12.00	300.00	100
4328-0300-100	3	76.20	3.67	93.22	2	300	20.68	n/a	1.88	2.80	14.00	350.00	100
4328-0400-100	4	101.60	4.61	117.09	2	300	20.68	n/a	2.57	3.82	18.00	450.00	100
4328-0500-100	5	127.00	5.67	144.02	2	300	20.68	n/a	4.09	6.08	24.00	600.00	100

Working pressure (W.P.) is temperature dependent. See the General Information section Table II - Pressure Re-Rating for increased Temperatures (Page 10) for more information.