

PETROLEUM HOSE

4348 FRACK OILFIELD FUEL DISCHARGE HOSE - 400 PSI - SΩ



CONSTRUCTION: Tube is nitrile, black and smooth, ARPM Class C. Cover is an EPDM/SBR blend. Reinforcement is a four-ply synthetic fabric with a static wire.

TEMPERATURE: -25°F (-32°C) to +180°F (+82°C)

BRANDING: Jason logo 4348 FRAC DISCHARGE WP 400 PSI 27.6 BAR. Red mylar longitudinal stripe.

SAFETY FACTOR: 3:1

APPLICATION: To discharge or convey water and oil slurry mixtures for the connections to frack tanks.

FEATURES:

- HD construction that handles up to 400 PSI applications.
- Cover is resistant to weathering and abrasion.
- Class C tube is oil resistant and will handle gasoline and other petroleum products having an aromatic content of 50%.
- Safety Ohm (SΩ) ground wire embedded into the hose wall to help prevent the build-up of static electricity. SΩ wire must be secured to ground to dissipate static electricity.

Part Number	I.D.		O.D.		Reinf. Plies	Max W.P. @ 68°F		Vacuum @ 68°F	Weight		Minimum Bend Radius		Std. Length (ft.)
	in.	mm	in.	mm		PSI	BAR		lb./ft.	KG/m	in.	mm	
4348-0300-100	3	76.20	3.87	93.30	4	400	27.60	n/a	2.52	3.74	18.00	457.20	100
4348-0400-100	4	101.60	4.76	120.90	4	400	27.60	n/a	2.83	4.21	24.00	600.00	100

Working pressure (W.P.) is temperature dependent. See the General Information section Table II - Pressure Re-Rating for increased Temperatures (Page 10) for more information.

SΩ = Safety Ohm

All sizes may not be stocked in all locations. Check with customer service for availability.

We disclaim any liability for use of our products in applications other than which they are designed.

WARNING: This product can expose you to chemicals including carbon black, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information visit www.P65WARNINGS.ca.gov