PETROLEUM HOSE



4368 HD OILFIELD LIQUID

4368 HD OILFIELD LIQUID MUD DISCHARGE HOSE - 600 PSI - SΩ



CONSTRUCTION: Tube is a synthetic rubber blend. Cover is CR. Reinforcement is a two-ply high-tensile synthetic textile with an anti-static copper wire.

TEMPERATURE: -31°F (-35°C) to +176°F (+80°C)

BRANDING: Jason logo 4368 HD OILFIELD LIQUID MUD (600 PSI) 41.4 BAR.

Red mylar longitudinal stripe.

SAFETY FACTOR: 4:1

APPLICATION: The discharge of high pressure liquid mud, mineral oils, etc. Also used in oil and gas exploration and oil rig platforms.

FEATURES:

- Cover is resistant to weathering and abrasion
- Cover is flame retardant
- Safety Ohm (SΩ) ground wire embedded into the hose wall to help prevent the build-up of static electricity.
 SΩ wire must be secured to ground to dissipate static electricity.

Not Recommended for Refined Petroleum Products!

Part Number	I.D.		O.D.		Reinf.	Max W.P. @ 68°F			Weight		Minimum Bend Radius		Std. Length
	in.	mm	in.	mm	Piles	PSI	BAR	@ 00 F	lb./ft.	KG/m	in.	mm	(ft.)
4368-0300-100	3	76.20	3.82	97.03	2	600	41.40	n/a	2.51	3.73	29.92	760.00	100
4368-0400-100	4	101.60	4.96	125.98	2	600	41.40	n/a	3.83	5.69	40.16	1020.00	100

Working pressure (W.P.) is temperature dependent. See the General Information section Table II - Pressure Re-Rating for increased Temperatures (Page 10) for more information.

 $S\Omega$ = Safety Ohm All sizes may not be stocked in all locations. Check with customer service for availability.

We disclaim any liability for use of our products in applications other than which they are designed.

73