

MATERIAL HANDLING HOSE

4375

CONCRETE PLACEMENT HOSE - 1300 PSI



CONSTRUCTION: Tube is a blend of synthetic and natural elastomers, black, smooth and anti-static. Cover is also a blend of synthetic and natural elastomers, black, smooth with a cloth impression and anti-static. Reinforcement is a 2 or 4-spiral high tensile steel wire.

TEMPERATURE: -22°F (-30°C) to +185°F (+85°C)

BRANDING: Jason logo 4375 1300 PSI WP WIRE CONCRETE PLACEMENT. Clear stripe with reversed lettering.

APPLICATION: For very high pressure concrete placement applications.

FEATURES:

- Tube and cover compounds are anti-static
- Tube is abrasion resistant
- Cover is abrasion, ozone and weather resistant
- Designed for high kink resistance and perfect flow

SAFETY FACTOR: 3:1

Part Number	I.D.		O.D.		Reinf. Spirals	Max W.P. @ 68°F		Vacuum @ 68°F	Weight		Minimum Bend Radius		Std. Length (ft.)
	in.	mm	in.	mm		PSI	BAR		lb./ft.	KG/m	in.	mm	
4375-0200-050	2	50.80	2.87	73.00	2	1300	89.6	n/a	1.95	2.91	16.10	410.00	50
4375-0200-100	2	50.80	2.87	73.00	2	1300	89.6	n/a	1.95	2.91	16.10	410.00	100
4375-0300-050	3	76.20	4.02	102.00	4	1300	89.6	n/a	3.63	5.40	24.00	610.00	50
4375-0300-100	3	76.20	4.02	102.00	4	1300	89.6	n/a	3.63	5.40	24.00	610.00	100
4375-0400-050	4	101.60	5.12	130.00	4	1300	89.6	n/a	5.31	7.90	32.30	820.00	50
4375-0400-100	4	101.60	5.12	130.00	4	1300	89.6	n/a	5.31	7.90	32.30	820.00	100

Working pressure (W.P.) is temperature dependent. See the General Information section Table II - Pressure Re-Rating for increased Temperatures (Page 10) for more information.

All sizes may not be stocked in all locations. Check with customer service for availability. We disclaim any liability for use of our products in applications other than which they are designed.

WARNING: This product can expose you to chemicals including carbon black, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information visit www.P65WARNINGS.ca.gov