

PETROLEUM HOSE

4413

OILFIELD VAC HOSE - 150 PSI



CONSTRUCTION: Tube is a nitrile blend. Cover is corrugated SBR blend. Reinforcement is a 4-ply high-tensile synthetic textile with a dual steel wire helix.

APPLICATION: The transfer of drilling mud or crude oil. Used in oil and gas exploration, fracking and wells service

TEMPERATURE: -22°F (-30°C) to +176°F (+80°C)

FEATURES:

BRANDING: Jason logo 4413 OILFIELD VACUUM
WP (150PSI) 10.35 BAR.
Red mylar longitudinal stripe.

- Cover is resistant to weathering and abrasion
- Tube can handle crude oil and drilling mud
- 1" to 6", full vacuum.

SAFETY FACTOR: 3:1

Not recommended for Refined Petroleum Products!

Part Number	I.D.		O.D.		Reinf. Plies	Max W.P. @ 68°F		Vacuum @ 68°F	Weight		Minimum Bend Radius		Std. Length (ft.)
	in.	mm	in.	mm		PSI	BAR		lb./ft.	KG/m	in.	mm	
4413-0150-100	1-1/2	38.10	1.78	45.21	4	150	10.35	28.00	0.72	1.07	4.53	110.00	100
4413-0200-100	2	50.80	2.41	61.21	4	150	10.35	28.00	1.06	1.58	5.71	170.00	100
4413-0250-100	2-1/2	63.50	3.17	80.52	4	150	10.35	28.00	1.42	2.12	7.68	210.00	100
4413-0300-100	3	76.20	3.58	90.93	4	150	10.35	28.00	1.81	2.70	9.45	230.00	100
4413-0400-100	4	101.60	4.58	116.33	4	150	10.35	28.00	2.60	3.87	13.39	400.00	100
4413-0600-100	6	154.20	6.75	171.45	4	150	10.35	28.00	5.09	7.57	25.59	675.00	100
4413-0800-020	8	203.20	8.84	224.54	4	150	10.35	28.00	9.09	13.52	35.43	1025.00	20
4413-1000-020	10	254.00	10.88	276.35	4	150	10.35	28.00	12.02	17.89	55.12	1450.00	20

Working pressure (W.P.) is temperature dependent. See the General Information section Table II - Pressure Re-Rating for increased Temperatures (Page 10) for more information.

All sizes may not be stocked in all locations. Check with customer service for availability.
We disclaim any liability for use of our products in applications other than which they are designed.

WARNING: This product can expose you to chemicals including carbon black, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information visit www.P65WARNINGS.ca.gov