

## **PETROLEUM HOSE**

## 4415

## **OIL RETURN HOSE SAE 100R4**







**CONSTRUCTION:** Tube is nitrile, black and smooth,

ARPM Class A. Cover is CR, black, ARPM Class B. Reinforcement is a two-ply synthetic fabric with a

wire helix.

**TEMPERATURE:** -40°F (-40°C) to +212°F (+100°C)

**BRANDING:** Jason logo 4415 SAE 100R4 RETURN LINE.

Red mylar longitudinal stripe.

**APPLICATION:** For oil return lines of hydraulic systems in industrial and agricultural systems.

## **FEATURES:**

- Cover is resistant to weathering and abrasion
- Class A tube is highly oil resistant and will handle petroleum products having an aromatic content of 50%
- All sizes are full vaccum

**SAFETY FACTOR: 3:1** 

Part Number	I.D.		O.D.		Reinf.	Max W.P. @ 68°F		Vacuum	Weight		Minimum Bend Radius		Std. Length
	in.	mm	in.	mm	Plies	PSI	BAR	@ 68°F	lb./ft.	KG/m	in.	mm	(ft.)
4415-0075-100	3/4	19.05	1.25	31.75	2	300	20.68	29.0	0.45	0.67	4.00	101.60	100
4415-0100-100	1	25.40	1.47	37.34	2	250	17.24	29.0	0.50	0.74	4.50	114.30	100
4415-0125-100	1-1/4	31.75	1.77	44.96	2	200	13.79	29.0	0.64	0.95	6.00	152.40	100
4415-0150-100	1-1/2	38.10	2.05	52.07	2	150	10.35	29.0	0.80	1.19	6.50	165.10	100
4415-0200-100	2	50.80	2.51	63.75	2	150	10.35	29.0	0.99	1.47	8.00	203.20	100

Working pressure (W.P.) is temperature dependent. See the General Information section Table II - Pressure Re-Rating for increased Temperatures (Page 10) for more information.

† Note: In the future this product will be moved to our hydraulic catalog.

The Series number will change from 4415 to 5040.