

MATERIAL HANDLING HOSE

4428

PLASTER AND GROUT HOSE



CONSTRUCTION: Tube is NR/SBR blend. Cover is a NR/SBR blend, pin-pricked. Reinforcement is four plies of synthetic textile with a static wire.

TEMPERATURE: -40°F (-40°C) to +158°F (+70°C)

BRANDING: Jason logo 4428 PLASTER GROUT WP 800 PSI 55.2 BAR. White mylar longitudinal stripe.

APPLICATION: Used for spraying plaster, grout, sand and gypsum.

FEATURES:

- Cover ozone and weather resistant
- Very good abrasion resistance
- Handles a variety of applications

SAFETY FACTOR: 3:1

Part Number	I.D.		O.D.		Reinf. Plies	Max W.P. @ 68°F		Vacuum @ 68°F	Weight		Minimum Bend Radius		Std. Length (ft.)
	in.	mm	in.	mm		PSI	BAR		lb./ft.	KG/m	in.	mm	
4428-0150-050	1-1/2	38.10	2.20	56.00	4	800	55.20	n/a	1.07	1.59	n/a	n/a	100
4428-0200-050	2	50.80	2.76	70.00	4	800	55.20	n/a	1.43	2.13	n/a	n/a	100
4428-0250-050	2-1/2	63.50	3.31	84.00	4	800	55.20	n/a	1.73	2.58	n/a	n/a	100

Working pressure (W.P.) is temperature dependent. See the General Information section Table II - Pressure Re-Rating for increased Temperatures (Page 10) for more information.

All sizes may not be stocked in all locations. Check with customer service for availability. We disclaim any liability for use of our products in applications other than which they are designed.

WARNING: This product can expose you to chemicals including carbon black, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information visit www.P65WARNINGS.ca.gov