

**4429**

**HOT TAR AND ASPHALT SUCTION HOSE - 150 PSI**



**CONSTRUCTION:** Tube is a special elastomer compound, black and smooth, that is synthetic oil, abrasion and heat resistant. Cover is a blend of synthetic elastomer compounds, black and smooth, and anti-static. Reinforcement is a two-or-four-ply high tensile cord with a steel wire helix.

**TEMPERATURE:** -22°F (-30°C) to +356°F (+180°C)

**BRANDING:** Jason logo 4429 HOT ASPHALT 356°F/180°C  
150 PSI 4:1. Embossed brand.

**APPLICATION:** Hose is specially designed for conveying hot tar and asphalt.

**FEATURES:**

- Cover is resistant to weathering and abrasion
- Cover is also anti-static, oil and heat resistant
- Special tube compound is heat (up to 356°F) and abrasion resistant.
- All sizes are full vacuum.

**SAFETY FACTOR:** 3:1

Part Number	I.D.		O.D.		Reinf. Plies	Max W.P. @ 68°F		Vacuum @ 68°F	Weight		Minimum Bend Radius		Std. Length (ft.)
	in.	mm	in.	mm		PSI	BAR		lb./ft.	KG/m	in.	mm	
4429-0200-100	2	50.80	2.72	69.00	2	150	10.35	29.0	1.77	2.65	10.00	254.00	100
4429-0300-100	3	76.20	3.78	96.00	2	150	10.35	29.0	2.82	4.21	15.00	380.00	100
4429-0400-100	4	101.60	4.80	122.00	4	150	10.35	29.0	3.82	5.70	20.00	510.00	100

**Working pressure (W.P.) is temperature dependent. See the General Information section Table II - Pressure Re-Rating for increased Temperatures (Page 10) for more information.**

All sizes may not be stocked in all locations. Check with customer service for availability.  
We disclaim any liability for use of our products in applications other than which they are designed.

**WARNING:** This product can expose you to chemicals including carbon black, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information visit [www.P65WARNINGS.ca.gov](http://www.P65WARNINGS.ca.gov)