

# **PETROLEUM HOSE**

## **OILFIELD PETRO WASTE SUCTION HOSE**





**CONSTRUCTION:** Tube is an NBR/SBR blend, black and smooth, oil resistant. Cover is an NBR/ PVC blend, black, flat corrugated w/ cloth impression, oil, abrasion, weather and ozone resistant. Reinforcement is a high tensile cord with a dual steel wire helix.

#### TEMPERATURE: -22°F (-30°C) to +185°F (+85°C)

**BRANDING:** Jason logo 4436 OILFIELD PETRO WASTE SUCTION WP (150PSI) 10.35 BAR. Blue mylar longitudinal stripe. **APPLICATION:** Designed to transfer petroleum waste, sediments, sludge, diluted mild chemi cals, brine and water in oil filled tank and waste pit recovery applications. Not suitable for refined petroleum products or high concentrations of chemicals.

#### FEATURES:

- Cover is resistant to weathering and abrasion
- Heat and ozone resistant
- Dual steel wires to ground the hose
- Light, flexible, easy-to-use

Part Number	I.D.		O.D.		Reinf.	Max W.P. @ 68°F			Weight		Minimum Bend Radius		Std. Length
	in.	mm	in.	mm	Plies	PSI	BAR	@ 68°F	lb./ft.	KG/m	in.	mm	(ft.)
4436-0200-100	2	50.80	2.48	63.00	2	150	10.35	26.0	1.04	1.55	5.00	128.00	100
4436-0300-100	3	76.20	3.50	89.00	2	150	10.35	26.0	1.75	2.60	7.50	190.00	100
4436-0400-100	4	101.60	4.53	115.00	2	150	10.35	26.0	2.19	3.25	10.00	255.00	100
4436-0600-020	6	152.40	6.65	169.00	2	150	10.35	26.0	4.41	6.57	24.00	608.00	20
4436-0600-050	6	152.40	6.65	169.00	2	150	10.35	26.0	4.41	6.57	24.00	608.00	50
4436-0600-100	6	152.40	6.65	169.00	2	150	10.35	26.0	4.41	6.57	24.00	608.00	100
4436-0800-020	8	203.20	8.82	224.00	2	150	10.35	26.0	7.36	10.97	32.00	812.00	20
4436-0800-050	8	203.20	8.82	224.00	2	150	10.35	26.0	7.36	10.97	32.00	812.00	50

Working pressure (W.P.) is temperature dependent. See the General Information section Table II - Pressure Re-Rating for increased Temperatures (Page 10) for more information.

All sizes may not be stocked in all locations. Check with customer service for availability. We disclaim any liability for use of our products in applications other than which they are designed.

#### WARNING: This product can expose you to chemicals including carbon black, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information visit www.P65WARNINGS.ca.gov

### SAFETY FACTOR: 3:1

74