

4449

FRAC WATER SUCTION HOSE



CONSTRUCTION: Tube and cover are an EPDM/SBR blend, smooth and black. Reinforcement is a two-ply synthetic fabric with a wire helix.

TEMPERATURE: -25°F (-32°C) to +185°F (+85°C)

BRANDING: Jason logo 4449 FRAC WATER SUCTION WP 75 PSI 5.18 BAR. Red mylar longitudinal stripe.

APPLICATION: For suction, recycling or disposal of flowback water.

FEATURES:

- EPDM blend cover makes it resistant to heat, weather and abrasion
- Lighter than standard water suction hose and more flexible
- Economical

SAFETY FACTOR: 3:1

Part Number	I.D.		O.D.		Reinf. Plies	Max W.P. @ 68°F		Vacuum @ 68°F	Weight		Minimum Bend Radius		Std. Length (ft.)
	in.	mm	in.	mm		PSI	BAR		lb./ft.	KG/m	in.	mm	
4449-0200-100	2	50.80	2.40	60.96	2	75	5.18	29.0	0.97	1.44	8.00	203.20	100
4449-0300-100	3	76.20	3.39	88.90	2	75	5.18	29.0	1.52	2.26	12.00	304.80	100
4449-0400-100	4	101.60	4.41	112.01	2	75	5.18	29.0	2.12	3.15	18.00	457.20	100
4449-0600-100	6	152.40	6.57	167.00	2	75	5.18	29.0	4.68	6.98	31.00	787.40	100

Working pressure (W.P.) is temperature dependent. See the General Information section Table II - Pressure Re-Rating for increased Temperatures (Page 10) for more information.

All sizes may not be stocked in all locations. Check with customer service for availability. We disclaim any liability for use of our products in applications other than which they are designed.

WARNING: This product can expose you to chemicals including carbon black, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information visit www.P65WARNINGS.ca.gov