





Green Pin® Rotating Hoist Ring UNC GR8

Grade 8 rotating hoist ring UNC



- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 5 x WLL
- **Finish:** painted red or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI^h CE
- **Note:** WLL indicated hereunder are given in the worst conditions of use, i.e. 90°

ADAUNC



| working load limit | diameter thread | width inside | length inside | diameter | length | thickness base | width outside | diameter base | diameter base | length inside | hex key | torque value | weight each |
|--------------------|-----------------|--------------|---------------|----------|--------|----------------|---------------|---------------|---------------|---------------|---------|--------------|-------------|
| t | a inch | b mm | c mm | d mm | e mm | f mm | g mm | h mm | i mm | j mm | mm | Nm | kg |
| 0.4 | 5/16 - 18UNC | 35 | 41 | 13 | 18 | 35 | 68 | 34 | 38 | 43 | 6 | 6.5 | 0.43 |
| 0.6 | 3/8 - 16UNC | 35 | 39 | 13 | 18 | 37 | 68 | 34 | 38 | 43 | 8 | 13 | 0.44 |
| 1 | 1/2 - 13UNC | 35 | 36 | 13 | 24 | 39 | 68 | 34 | 38 | 43 | 10 | 22 | 0.46 |
| 1.7 | 5/8 - 11UNC | 35 | 42 | 13 | 31 | 43 | 68 | 34 | 38 | 52 | 13 | 55 | 0.54 |
| 2.5 | 3/4 - 10UNC | 35 | 38 | 13 | 31 | 47 | 68 | 34 | 38 | 52 | 16 | 110 | 0.55 |
| 3.5 | 7/8 - 9UNC | 53 | 57 | 20 | 37 | 69 | 105 | 49 | 56 | 71 | 19 | 150 | 1.88 |
| 4.5 | 1 - 8UNC | 53 | 55 | 20 | 43 | 71 | 105 | 49 | 56 | 71 | 19 | 190 | 1.93 |