





## Green Pin® Grab Hook E EN 1677-1 GR8

### Grade 8 eye grab hook EN 1677-1

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard :** EN 1677-1
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 \* MPI<sup>b</sup> \* DGUV \*



CRO



for chain diameter		working load limit	length	inside length eye	inside width eye	opening	thickness	width	width outside	length outside	width	thickness	weight each
mm	inch												
6	7/32	1.12	41	24	23	8	24	20	42	94	9	6	0.25
7 - 8	1/4 - 5/16	2	53	27	26	10	33	23	53	115	10	8	0.45
10	3/8	3.2	65	38	36	12	40	29	66	146	14	10	0.91
13	1/2	5.4	83	42	41	15	56	40	88	183	16	12	1.99
16	5/8	8.2	103	44	41	18	66	43	96	211	20	20	2.49
20	3/4	12.8	130	37	37	22	75	48	128	241	26	26	4.3
22	7/8	15.5	120	44	44	25	77	57	132	247	26	26	8.5
26	1	21.6	158	46	46	30	100	82	177	320	32	32	14.7
32	1 1/4	32.8	210	57	57	38	91	88	215	395	39	39	18

\* Excluding sizes 20 mm, 22 mm, 26 mm and 32 mm





## Green Pin® Grab Hook CL EN 1677-1 GR8

### Grade 8 clevis grab hook EN 1677-1

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard :** EN 1677-1
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI<sup>b</sup>



CRC



for chain diameter		working load limit	length	width	width outside	opening	thickness	width	width outside	length outside	diameter pin	weight each
mm	inch											
6	7/32	1.12	52	7	28	7	24	19	42	86	8	0.28
7 - 8	1/4 - 5/16	2	64	9	32	10	33	23	53	104	9	0.45
10	3/8	3.2	75	12	42	12	40	29	66	127	13	0.88
13	1/2	5.4	103	15	54	15	56	40	88	173	16	2.17
16	5/8	8.2	127	19	68	18	65	43	96	208	20	2.81