




## Green Pin® Sling Hook SE EN 1677-2 GR8

### Grade 8 swivel sling hook EN 1677-2

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard :** EN 1677-2
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI<sup>®</sup> DGUV
- **Note:** equipped with needle roller thrust bearing to enable rotation under load



CSE



for chain diameter		working load limit	length	length inside	width inside	width opening	thickness	width	width outside	length outside	diameter	thickness	weight each
mm	inch												
5 - 6	3/16 - 7/32	1.12	100	33	32	26	15	20	72	164	12	6	0.55
7 - 8	1/4 - 5/16	2	126	39	37	30	20	24	87	200	14	8	1
10	3/8	3.2	159	47	48	33	24	29	106	250	16	11	1.9
13	1/2	5.4	189	59	58	37	32	39	133	307	21	14	3.39
16	5/8	8.2	216	68	73	44	40	44	165	352	25	17	6.25
18 - 20	3/4	12.8	263	87	82	61	49	62	208	437	25	22	10.5




## Green Pin® Sling Hook SCL EN 1677-2 GR8

### Grade 8 swivel sling hook with clevis EN 1677-2

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard :** EN 1677-2
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI<sup>®</sup> DGUV
- **Note:** equipped with needle roller thrust bearing to enable rotation under load



CSECA



for chain diameter		working load limit	length	width	width opening	thickness	width	width outside	width outside	length	diameter pin	weight each
mm	inch											
5	3/16	0.8	126	7	26	15	20	56	72	159	6	0.56
6	7/32	1.12	125	7	26	15	20	56	72	159	8	0.56
7/8	1/4 - 5/16	2	153	9	30	20	24	65	87	194	9	0.99
10	3/8	3.2	188	12	33	24	29	79	106	240	13	1.95
13	1/2	5.4	224	15	37	32	39	96	133	294	16	3.54
16	5/8	8.2	270	19	44	40	44	121	165	350	20	6.61