




Green Pin® Flat Web Sling Hook GR8

Grade 8 flat web sling hook



CST



- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted yellow or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI^b

working load limit	length	inside width eye	width opening	thickness	width inside	width outside	width outside	length outside	width inside	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
3	132	79	34	40	75	113	148	199	25	2.63




Green Pin® Flat Web Sling Safety Hook GR8

Grade 8 flat web sling self locking hook



XLS



- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted yellow or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI^b

working load limit	length	width	width opening	thickness	width	width outside	width outside	length outside	length inside	diameter pin	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
2	161	62	47	32	35	94	111	222	18	16	2.11