



G-6240



Green Pin® wire rope clips

generally to EN 13411-5 Type B

- **Material** : Bridge : drop forged high tensile steel SAE 1045
U-bolt : SAE 1015
- **Standard** : EN 13411-5 Type B
Formerly U.S. Federal Specification FF-C-450D
- **Finish** : Hot dipped galvanized
U-bolt and/or nuts for diameter bow 5, 6, 8 and 10 are electro galvanized
- **Certification** : 2.1

diameter wire rope	diameter	length bow	width inside	length thread	length base	thickness base	height base	weight per 100 pcs
mm	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
4	5	24	12	11	24	21	10	2
5	6	31	15	13	29	24	13	4
7	8	34	19	13	37	30	18	8
8	10	45	22	19	43	33	19	13
10	11	49	26	19	49	42	25	19
11	12	60	30	25	58	46	26	33
13	13	61	30	25	58	48	31	34
15	14	72	33	32	63	52	31	45
16	14	74	33	32	64	54	36	45
20	16	86	38	37	72	57	38	68
22	19	98	45	41	80	62	40	108
26	19	108	48	46	88	67	47	113
30	19	117	51	51	91	73	48	140
34	22	130	59	54	105	79	56	207
36	22	140	60	59	108	79	58	234
40	22	147	66	60	112	85	64	254
42	25	161	70	67	121	92	67	329
46	29	174	78	70	134	97	76	441
52	32	195	86	78	150	113	85	603
58	32	213	98	81	162	116	100	707
65	32	227	105	87	168	119	113	806
72	32	243	112	91	174	127	124	1015
78	38	271	121	98	194	135	136	1472

diameter wire rope	diameter	length bow	width inside	length thread	length base	thickness base	height base	weight per 100 pcs
inch	a inch	b inch	c inch	d inch	e inch	f inch	g inch	lbs
1/8	3/16	15/16	15/32	7/16	15/16	13/16	13/32	4.4
3/16	1/4	1 7/32	19/32	1/2	1 5/32	15/16	1/2	8.8
1/4	5/16	1 11/32	3/4	1/2	1 15/32	1 3/16	23/32	17.6
5/16	13/32	1 25/32	7/8	3/4	1 11/16	1 5/16	3/4	28.7
3/8	7/16	1 15/16	1 1/32	3/4	1 15/16	1 21/32	31/32	42
7/16	15/32	2 3/8	1 3/16	31/32	2 9/32	1 13/16	1 1/32	73
1/2	1/2	2 13/32	1 3/16	31/32	2 9/32	1 7/8	1 7/32	75
9/16	9/16	2 27/32	1 5/16	1 1/4	2 15/32	2 1/16	1 7/32	99
5/8	9/16	2 29/32	1 5/16	1 1/4	2 17/32	2 1/8	1 13/32	99
3/4	5/8	3 3/8	1 1/2	1 15/32	2 27/32	2 1/4	1 1/2	150
7/8	3/4	3 27/32	1 25/32	1 5/8	3 5/32	2 7/16	1 9/16	238
1	3/4	4 1/4	1 7/8	1 13/16	3 15/32	2 5/8	1 7/8	249
1 1/8	3/4	4 19/32	2	2	3 19/32	2 7/8	1 7/8	309
1 1/4	7/8	5 1/8	2 5/16	2 1/8	4 1/8	3 1/8	2 7/32	456
1 3/8	7/8	5 1/2	2 3/8	2 5/16	4 1/4	3 1/8	2 9/32	516
1 1/2	7/8	5 25/32	2 19/32	2 3/8	4 13/32	3 11/32	2 17/32	560
1 5/8	31/32	6 11/32	2 3/4	2 5/8	4 3/4	3 5/8	2 5/8	725
1 3/4	1 5/32	6 27/32	3 1/16	2 3/4	5 9/32	3 13/16	3	972
2	1 1/4	7 11/16	3 3/8	3 1/16	5 29/32	4 7/16	3 11/32	1329
2 1/4	1 1/4	8 3/8	3 27/32	3 3/16	6 3/8	4 9/16	3 15/16	1559
2 1/2	1 1/4	8 15/16	4 1/8	3 7/16	6 5/8	4 11/16	4 7/16	1777
2 3/4	1 1/4	9 9/16	4 13/32	3 19/32	6 27/32	5	4 7/16	2238
3	1 1/2	10 21/32	4 3/4	3 27/32	7 5/8	5 5/16	5 11/32	3245