

LOCKING LEVER PUMP COUPLINGS

- Full Vacuum Rated
- 30° Articulation
- Type B Industrial
- NBR O-Ring
- Lock Pin Lever
- Interchangeable
- Galvanized
- Quick and Easy Connections

FULL ASSEMBLY*¹



Size (inch)	Part No.
2	BGA200
3	BGA300
4	BGA400
6	BGA600
8	BGA800

* includes O-Ring

LEVER RING*



Size (inch)	Part No.
2	BLR200
3	BLR300
4	BLR400
6	BLR600
8	BLR800

* with safety clip

MALE BALL x FLANGE (150 ASA)



Size (inch)	Part No.
4	BMF400
6	BMF600
8	BMF800

Not recommended for chemicals or hazardous materials.

FEMALE SOCKET* x FLANGE (150 ASA)¹



Size (inch)	Part No.
4	BFF400
6	BFF600
8	BFF800

* includes O-Ring

150 ASA FLANGE DIMENSIONS

Size		Bolt Circle Diameter		No. of Bolts	Diameter of Bolts		Diameter of Bolt Holes		Flange O.D.		Weight	
inch	mm	inch	mm		inch	mm	inch	mm	inch	mm	lbs.	kg.
4	101.60	7-1/2	190.50	8	5/8	15.88	3/4	19.05	9	228.60	13	29.25
6	152.40	9-1/2	241.30	8	3/4	19.05	7/8	22.23	11	279.40	19-1/2	43.88
8	203.20	11-3/4	298.45	8	3/4	19.05	7/8	22.23	13-1/2	342.90	30	67.50

¹This product can expose you to chemicals including carbon black, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information visit www.P65WARNINGS.ca.gov

All sizes may not be stocked in all locations. Check with customer service for availability.
We disclaim any liability for use of our products in applications other than which they are designed.