

## BRASS BALL VALVES



Part Number	Size (inch)	A (mm)	Thread
BV025BF	1/4	6.4	1/4 NPT
BV038BF	3/8	9.9	3/8 NPT
BV050BF	1/2	14.0	1/2 NPT
BV075BF	3/4	19.0	3/4 NPT
BV100BF	1	24.0	1 NPT
BV125BF	1-1/4	31.0	1-1/4 NPT
BV150BF	1-1/2	38.0	1-1/2 NPT
BV200BF	2	49.0	2 NPT
BV250BF	2-1/2	64.0	2-1/2 NPT
BV300BF	3	79.0	3 NPT
BV400BF	4	99.0	4 NPT

Ball Valve Components		
1	Valve Body	Brass
2	Valve Cap	Brass
3	O-Ring	PTFE
4	Ball	Brass, chrome plated
5	Stem Spacer/Gasket	PTFE
6	O-Ring	PTFE
7	Stem	Brass
8	Nut	Brass
9	Cap	Brass
10	Handle	Carbon Steel

### FEATURES:

- Sizes to 2" rated 600 WOG,
- 2-1/2", 3" and 4" rated 400 WOG
- Temperature Range: Up to 150° F (66° C)
- Brass ball is chromium plated.
- Ball seat is Teflon®\*

Teflon is a registered trademark of DuPont

**WARNING!** Brass should never be exposed to use of any materials containing ammonia due to susceptibility of brass for stress corrosion cracking. This attack can cause sudden and catastrophic failure of the assembly leading to property damage, injury, or death.

**WARNING!** Brass products can expose you to chemicals including lead, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information visit [www.P65WARNINGS.ca.gov](http://www.P65WARNINGS.ca.gov)

**All sizes may not be stocked in all locations. Check with customer service for availability.**  
**We disclaim any liability for use of our products in applications other than which they are designed.**