




UCSCT



## Green Pin Tycan® Sling Hook CL GR10

### Grade 10 clevis sling hook

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted blue
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI<sup>1</sup>
- **Compatible with:** FCHLIFT; 2.6t, 4t and 6.8t


for chain size	working load limit	length	width	width opening	thickness	width	width outside	width outside	length outside	diameter pin	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
11x15	2.6	112	17	30	20	24	44	87	158	13	0.73
11x20	4	129	22	33	24	29	57	106	186	16	1.31
13x30	6.8	159	32	37	32	39	74	133	235	20	2.56

In inch

for chain size	working load limit	length	width	width opening	thickness	width	width outside	width outside	length outside	diameter pin	weight each
inch	t	a inch	b inch	c inch	d inch	e inch	f inch	g inch	h inch	i inch	lbs
7/16 X 19/32	2.6	4 12/32	21/32	1 3/16	25/32	15/16	1 3/4	3 7/16	6 7/32	1/2	1.61
7/16 X 25/32	4	5 3/32	7/8	1 5/16	15/16	1 5/32	2 1/4	4 3/16	7 5/16	5/8	2.88
1/2 X 1 3/16	6.8	6 1/4	1 1/4	1 15/32	1 1/4	1 17/32	2 29/32	5 1/4	9 1/4	25/32	5.64



P-6720A



## Clevis Hook for Green Pin Tycan®

### Grade 10 clevis hook with safety latch for use with Green Pin Tycan® Chain

- **Material:** alloy steel
- **Safety factor:** MBL equals 4 x WLL and MBL equals 2 x Lashing Capacity
- **Finish:** painted blue
- **Certification:** 2.1 2.2 CE
- **Compatible with:** FCHLIFT1525, FCHLASH1525

for chain size	working load limit	lashing capacity	length	width	width	width outside	width outside	length outside	diameter pin	weight each
mm	t	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
15x25	5	10	110	26	40	62	113	179	16	1.25

In inch

for chain size	working load limit	lashing capacity	length	width	width	width outside	width outside	length outside	diameter pin	weight each
inch	t	t	a inch	b inch	c inch	d inch	e inch	f inch	g inch	lbs
19/32 X 1	5	10	4 11/32	1	1 9/16	2 7/16	4 29/64	7	5/8	2.75