



Green Pin® Foundry Hook E

Grade 8 eye foundry hook



Highlights

- ✓ Reliable Green Pin® quality and support
- ✓ Superior stock availability of 99%

Description

The Green Pin® Foundry Hook E is a grade 8 eye foundry hook. The throats are designed to accommodate standard trunnions, whereas the tips enable easy insertion into the holes of the melting pots. These hooks must be used for specific applications in foundries as they do not have safety latches. The Green Pin® Foundry Hook E is available in a range to suit 6 mm up to 32 mm grade 8 chain.

Product details

Productcode	CFO
Material	alloy steel, Grade 8, quenched and tempered
Safety factor	MBL equals 4 x WLL
Finish	painted white
Certification	2.1 2.2 3.1 MTCa MPIb DGUV
Note	from 8.2 t without flat part

www.greenpin.com



Green Pin® Foundry Hook E

Technical specifications in millimeters

Article code	working load limit	for chain diameter	A length	B diameter eye inside	C opening hook	D thickness	E width	F diameter eye outside	G width outside	H length	I thickness	Net weight (kg)
GPCFO6	1,12	6	93	19	48	17	21	38	97	124	7	0.33
GPCFO7/8	2	7 - 8	125	25	64	22	28	50	129	165	9	0.78
GPCFO10	3,2	10	157	34	79	27	35	65	161	208	11	1.50
GPCFO13	5,4	13	190	44	95	35	45	84	198	254	13	3.00
GPCFO16	8,2	16	205	35	95	45	52	88	204	284	24	4.16
GPCFO18/20	12,8	18 - 20	235	40	111	53	55	92	228	315	25	7.80
GPCFO22	15,5	22	265	46	123	66	71	110	258	268	32	9.87
GPCFO26	21,6	26	305	54	133	65	81	120	277	420	33	13.8
GPCFO32	32,8	32	327	60	155	84	96	131	333	459	35	24.5

www.greenpin.com



Green Pin® Foundry Hook E

Technical specifications in inches

Article code	working load limit	for chain diameter (inch)	A length (inch)	B diameter eye inside (inch)	C opening hook (inch)	D thickness (inch)	E width (inch)	F diameter eye outside (inch)	G width outside (inch)	H length (inch)	I thickness (inch)	Net weight (LBS)
GPCFO6	1,12	7/32	3 21/32	3/4	1 7/8	21/32	13/16	1 1/2	3 13/16	4 7/8	9/32	0.73
GPCFO7/8	2	1/4 - 5/16	4 29/32	31/32	2 17/32	7/8	1 3/32	1 31/32	5 3/32	6 1/2	11/32	1.72
GPCFO10	3,2	3/8	6 3/16	1 11/32	3 1/8	1 1/16	1 3/8	2 9/16	6 11/32	8 3/16	7/16	3.31
GPCFO13	5,4	1/2	7 15/32	1 23/32	3 3/4	1 3/8	1 25/32	3 5/16	7 25/32	10	1/2	6.62
GPCFO16	8,2	5/8	8 1/16	1 3/8	3 3/4	1 25/32	2 2/16	3 15/32	8 1/32	11 3/16	15/16	9.18
GPCFO18/20	12,8	3/4	9 1/4	1 9/16	4 3/8	2 3/32	2 5/32	3 5/8	8 31/32	12 13/32	31/32	17.2
GPCFO22	15,5	7/8	10 7/16	1 13/16	4 27/32	2 19/32	2 25/32	4 11/32	10 5/32	10 9/16	1 1/4	21.8
GPCFO26	21,6	1	12	2 1/8	5 1/4	2 9/16	3 3/16	4 23/32	10 29/32	16 17/32	1 5/16	30.4
GPCFO32	32,8	1 1/4	12 7/8	2 3/8	6 3/32	3 5/16	3 25/32	5 5/32	13 1/8	18 1/16	1 3/8	54.0



Technical drawing

Green Pin® Foundry Hook E

