



Green Pin® Round Web Sling Connector

Grade 8 round web sling connector



Highlights

- ✓ Reliable Green Pin® quality and support
- ✓ Superior stock availability of 99%

Description

The Green Pin® Round Web Sling Connector is a grade 8 round web sling connector. This web link is suitable with an omega link for connecting round or flat webbing slings to master links. Direct connection to clevis hooks is also possible. The Green Pin® Round Web Sling Connector is available in a range with a working load limit from 2 t. up to 8.2 t.

Product details

Productcode	COS
Material	bow and pin alloy steel, Grade 8, Polar Quality, quenched and tempered
Safety factor	MBL equals 4 x WLL
Finish	painted white
Certification	2.1 2.2 3.1 MTCa MPIb

www.greenpin.com



Green Pin® Round Web Sling Connector

Technical specifications in millimeters

Article code	working load limit	Net weight	A width	B diameter pin	C width	D length inside	E width inside	F length outside	G thickness	H width outside	Net weight (kg)
GPCOS60	2	0.17	14	9	33	35	23	66	15	59	0.17
GPCOS90	3,2	0.37	18	13	44	45	30	86	20	75	0.37
GPCOS150	5.4	0.72	22	16	57	59	38	107	25	94	0.72
GPCOS240	8,2	1.35	28	20	70	72	48	133	31	117	1.35

www.greenpin.com



Green Pin® Round Web Sling Connector

Technical specifications in inches

Article code	working load limit	Net weight	A width (inch)	B diameter pin (inch)	C width (inch)	D length inside (inch)	E width inside (inch)	F length outside (inch)	G thickness (inch)	H width outside (inch)	Net weight (LBS)
GPCOS60	2	0.38	9/16	11/32	1 5/16	1 3/8	29/32	2 19/32	19/32	2 5/16	0.38
GPCOS90	3,2	0.82	23/32	1/2	1 23/32	1 25/32	1 3/16	3 3/8	25/32	2 15/16	0.82
GPCOS150	5,4	1.59	7/8	5/8	2 1/4	2 5/16	1 1/2	4 7/32	31/32	3 11/16	1.59
GPCOS240	8,2	2.98	1 3/32	25/32	2 3/4	2 27/32	1 7/8	5 1/4	1 7/32	4 19/32	2.98

www.greenpin.com



Green Pin® Round Web Sling Connector

Technical drawing

