



Green Pin® Sling Hook CL EN1677-2

Grade 8 clevis sling hook EN1677-2



Highlights

- ✓ Reliable Green Pin® quality and support
- ✓ Superior stock availability of 99%

Description

The Green Pin® Sling Hook CL EN1677-2 is a grade 8 clevis sling hook according to European standard for components for sling EN 1677-2. The sling hook can be used for general lifting applications. It can be quickly connected to the load lifting points thanks to its easy operating latch, which guarantees full safety. To connect simply push the latch, connect the hook to the lifting point, and release the latch. The forged latch guarantees a longer lifespan. It strongly limits the risk that the operator uses the hook without latch. The latch is fitted with a stainless steel spring and a sturdy pin. The clevis design enables a direct connection to grade 8 chain. The Green Pin® Sling Hook CL EN1677-2 is available in a range to suit 6 mm up to 22 mm grade 8 chain.

Product details

Productcode	CSC
Material	alloy steel, Grade 8, quenched and tempered
Safety factor	MBL equals 4 x WLL
Finish	painted white
Certification	2.1 2.2 3.1 MTCa MPIb DGUV



Green Pin® Sling Hook CL EN1677-2

Technical specifications in millimeters

Article code	working load limit	for chain diameter	A length	B width	C opening hook	D thickness	E width	F width outside	G width outside	H length outside	I diameter pin	Net weight (kg)
GPCSC5	0,8	5	74	7	26	15	20	28	72	108	8	0.29
GPCSC6	1,12	6	74	7	26	15	20	28	72	108	8	0.29
GPCSC7/8	2	7 - 8	95	9	30	20	24	32	87	136	9	0.58
GPCSC10	3,2	10	113	12	33	24	29	42	106	164	13	1.08
GPCSC13	5,4	13	139	15	37	32	39	54	133	208	16	2.12
GPCSC16	8,2	16	162	19	44	40	44	68	165	240	20	3.67
GPCSC18/20	12,8	18 - 20	199	23	61	49	62	82	208	305	24	7.32
GPCSC22	15,5	22	239	25	75	54	65	97	242	350	28	10.7



Green Pin® Sling Hook CL EN1677-2

Technical specifications in inches

Article code	working load limit	for chain diameter (inch)	A length (inch)	B width (inch)	C opening hook (inch)	D thickness (inch)	E width (inch)	F width outside (inch)	G width outside (inch)	H length outside (inch)	I diameter pin (inch)	Net weight (LBS)
GPCSC5	0,8	3/16	2 29/32	9/32	1 1/32	19/32	25/32	1 3/32	2 27/32	4 1/4	5/16	0.64
GPCSC6	1,12	7/32	2 29/32	9/32	1 1/32	19/32	25/32	1 3/32	2 27/32	4 1/4	5/16	0.64
GPCSC7/8	2	1/4 - 5/16	3 3/4	11/32	1 3/16	25/32	15/16	1 1/4	3 7/16	5 11/32	11/32	1.29
GPCSC10	3,2	3/8	4 7/16	15/32	1 5/16	15/16	1 5/32	1 21/32	4 3/16	6 15/32	1/2	2.38
GPCSC13	5,4	1/2	5 15/32	19/32	1 15/32	1 1/4	1 17/32	2 1/8	5 1/4	8 3/16	5/8	4.68
GPCSC16	8,2	5/8	6 3/8	23/32	1 23/32	1 9/16	1 23/32	2 11/16	6 1/2	9 7/16	25/32	8.09
GPCSC18/20	12,8	3/4	7 27/32	29/32	2 13/32	1 15/16	2 7/16	3 7/32	8 3/16	12	15/16	16.2
GPCSC22	15,5	7/8	9 13/32	31/32	2 15/16	2 1/8	2 9/16	3 13/16	9 17/32	13 25/32	1 3/32	23.6



Green Pin® Sling Hook CL EN1677-2

Technical drawing

