

Green Pin BigMouth<sup>®</sup> Dee Shackle BN Dee shackle with a longer inside length, wider mouth and safety bolt



#### Highlights

- Longer inside length
- Perfect for lifting steel sheet pile walls
- Galvanization assures long-term durability
- Double safety (cotter pin & safety bolt)
- Suitable for one-leg systems only

#### Description

The Green Pin BigMouth<sup>®</sup> Dee Shackle BN is ideal for use in situations where a lifting point is out of reach for a standard shackle. The BigMouth<sup>®</sup> Dee Shackle BN has a wider inside width and a longer inside length enabling you to connect the shackle to non-typical lifting points. Such lifting points are for example often found in the steel sheet pile wall industry. The lifting points on the pile walls are usually set at a depth at which only a Green Pin BigMouth<sup>®</sup> Dee Shackle BN can be used to complete the job. The Green Pin BigMouth<sup>®</sup> Dee Shackle BN is fitted with a safety bolt. Long-term durability is assured due to the galvanization of the Green Pin BigMouth<sup>®</sup> Dee Shackle BN. The shackle conforms to a range of certifications. The Green Pin BigMouth<sup>®</sup> Dee Shackle BN is suitable for both one-leg and multi-leg systems and is available in a range with a working load limit from 4.6 up to 15.5 ton.

#### **Product details**

Productcode	G-4553								
Material	bow and pin alloy steel, Grade 8, quenched and								
	tempered								
Safety factor	MBL equals 5 x WLL								
Finish	hot dipped galvanized								
Certification	2.1 2.2 3.1 MTCa CE								



## Green Pin BigMouth<sup>®</sup> Dee Shackle BN

## Technical specifications in milimeters

Milde cole	workingload	Init Netweight	Adiameterbo	B diameter pir	diameter eve	owidtheye	E. widthirside	Flendtrinside	Glength .	HIEROTHDOL	, thickness h	42
LDGDMB19	4,6	1.50	19	22	46	19	70	116	169	154	19	رمين 1.50
LDGDMB25	8,6	3.13	25	28	59	25	83	140	208	190	25	3.13
LDGDMB38	15,5	9.42	38	42	88	38	115	178	281	257	19	9.42

www.greenpin.com



## Green Pin BigMouth<sup>®</sup> Dee Shackle BN

## Technical specifications in inches


Article code	workingload	hetweight	Adiameter	Baismeet	chanete even	unch Dwidthere		ren Flength Inst	e linch	Hendroot	hem thickness f	C
LDGDMB19	4,6	3.30	3/4	7/8	1 13/16	3/4	2 3/4	4 9/16	6 21/32	6 1/16	3/4	3.30
LDGDMB25	8,6	6.90	1	1 1/8	2 5/16	1	3 1/4	5 1/2	8 3/16	7 15/32	31/32	6.90
LDGDMB38	15,5	20.8	11/2	1 5/8	3 15/32	1 1/2	4 17/32	7	11 1/16	10 1/8	3/4	20.8

www.greenpin.com



**Technical drawing** 

# Green Pin BigMouth<sup>®</sup> Dee Shackle BN



www.greenpin.com