



## Green Pin® Wire Rope Clip

Wire rope clip generally to EN 13411-5 Type B



## Highlights

- ✓ High tensile steel
- ✓ Ribs prevent sliding of wire rope
- ✓ Galvanization assures long-term durability
- ✓ Generally to EN 13411-5 Type B
- ✓ Superior stock availability of 99%

## Description

The Green Pin® Wire Rope Clip is a wire rope clip, generally to EN 13411-5 Type B. This wire rope clip is safer to work with as the ribs on the bearing surface of the clip prevent sliding of the wire rope. Furthermore, the wire rope clip is made from high tensile steel, while galvanization ensures its long-term durability. The Green Pin® Wire Rope Clip is available in a range for wire rope diameters of 3 up to 78 mm.

## Product details

<b>Productcode</b>	G-6240
<b>Material</b>	Bridge: drop forged high tensile steel SAE 1045U-bolt: SAE 1015
<b>Finish</b>	Hot dipped galvanizedU-bolt and/or nuts for diameter bow 5, 6, 8 and 10 mm are electro-galvanized
<b>Certification</b>	<b>2.1</b>
<b>Standard</b>	generally to EN 13411-5 Type BFormerly US Federal Specification FF-C-450D

[www.greenpin.com](http://www.greenpin.com)



## Green Pin® Wire Rope Clip

### Technical specifications in millimeters

Article code	diameter wire rope	Net weight	A diameter	B length bow	C width inside	D length thread	E length base	F thickness base	G height base	Net weight (kg)
CLGRP03	3 - 4	0.03	5	24	12	11	24	21	10	0.03
CLGRP05	5	0.07	6	31	15	13	29	24	13	0.07
CLGRP06	6 - 7	0.08	8	34	19	13	37	30	18	0.08
CLGRP08	8	0.12	10	45	22	19	43	33	19	0.12
CLGRP10	9 - 10	0.21	11	49	26	19	49	42	25	0.21
CLGRP11	11	0.33	12	60	30	25	58	46	26	0.33
CLGRP12	12 - 13	0.33	13	61	30	25	58	48	31	0.33
CLGRP14	14 - 15	0.46	14	72	33	32	63	52	31	0.46
CLGRP16	16	0.46	14	74	33	32	64	54	36	0.46
CLGRP19	18 - 20	0.64	16	86	38	37	72	57	38	0.64
CLGRP22	22	0.96	19	98	45	41	80	62	40	0.96
CLGRP25	24 - 26	1.15	19	108	48	46	88	67	47	1.15



## Green Pin® Wire Rope Clip

### Technical specifications in millimeters

Article code	diameter wire rope	Net weight	A diameter	B length bow	C width inside	D length thread	E length base	F thickness base	G height base	Net weight (kg)
CLGRP28	28 - 30	1.27	19	117	51	51	91	73	48	1.27
CLGRP32	32 - 34	1.97	22	130	59	54	105	79	56	1.97
CLGRP35	36	2.07	22	140	60	59	108	79	58	2.07
CLGRP38	38 - 40	2.54	22	147	66	60	112	85	64	2.54
CLGRP42	41 - 42	3.22	25	161	70	67	121	92	67	3.22
CLGRP45	44 - 46	4.18	29	174	78	70	134	97	76	4.18
CLGRP50	48 - 52	6.02	32	195	86	78	150	113	85	6.02
CLGRP56	56 - 58	7.76	32	213	98	81	162	116	100	7.76
CLGRP64	62 - 65	8.62	32	227	105	87	168	119	113	8.62
CLGRP69	68 - 72	10.2	32	243	112	91	174	127	124	10.2
CLGRP75	75 - 78	12.7	38	271	121	98	194	135	136	12.7



## Green Pin® Wire Rope Clip

### Technical specifications in inches

Article code	diameter wire rope (inch)	Net weight	A diameter (inch)	B length bow (inch)	C width inside (inch)	D length thread (inch)	E length base (inch)	F thickness base (inch)	G height base (inch)	Net weight (LBS)
CLGRP03	1/8	0.07	3/16	15/16	15/32	7/16	15/16	13/16	13/32	0.07
CLGRP05	3/16	0.15	1/4	1 7/32	19/32	1/2	1 5/32	15/16	1/2	0.15
CLGRP06	1/4	0.19	5/16	1 11/32	3/4	1/2	1 15/32	1 3/16	23/32	0.19
CLGRP08	5/16	0.27	13/32	1 25/32	7/8	3/4	1 11/16	1 5/16	3/4	0.27
CLGRP10	3/8	0.46	7/16	1 15/16	1 1/32	3/4	1 15/16	1 21/32	31/32	0.46
CLGRP11	7/16	0.73	15/32	2 3/8	1 3/16	31/32	2 9/32	1 13/16	1 1/32	0.73
CLGRP12	1/2	0.73	1/2	2 13/32	1 3/16	31/32	2 9/32	1 7/8	1 7/32	0.73
CLGRP14	9/16	1.01	9/16	2 27/32	1 5/16	1 1/4	2 15/32	2 1/16	1 7/32	1.01
CLGRP16	5/8	1.01	9/16	2 29/32	1 5/16	1 1/4	2 17/32	2 1/8	1 13/32	1.01
CLGRP19	3/4	1.42	5/8	3 3/8	1 1/2	1 15/32	2 27/32	2 1/4	1 1/2	1.42
CLGRP22	7/8	2.13	3/4	3 27/32	1 25/32	1 5/8	3 5/32	2 7/16	1 9/16	2.13
CLGRP25	1	2.54	3/4	4 1/4	1 7/8	1 13/16	3 15/32	2 5/8	1 7/8	2.54



## Green Pin® Wire Rope Clip

### Technical specifications in inches

Article code	diameter wire rope (inch)	Net weight	A diameter (inch)	B length bow (inch)	C width inside (inch)	D length thread (inch)	E length base (inch)	F thickness base (inch)	G height base (inch)	Net weight (LBS)
CLGRP28	1 1/8	2.81	3/4	4 19/32	2	2	3 19/32	2 7/8	1 7/8	2.81
CLGRP32	1 1/4	4.35	7/8	5 1/8	2 5/16	2 1/8	4 1/8	3 1/8	2 7/32	4.35
CLGRP35	1 3/8	4.55	7/8	5 1/2	2 3/8	2 5/16	4 1/4	3 1/8	2 9/32	4.55
CLGRP38	1 1/2	5.59	7/8	5 25/32	2 19/32	2 3/8	4 13/32	3 11/32	2 17/32	5.59
CLGRP42	1 5/8	7.11	31/32	6 11/32	2 3/4	2 5/8	4 3/4	3 5/8	2 5/8	7.11
CLGRP45	1 3/4	9.21	1 5/32	6 27/32	3 1/16	2 3/4	5 9/32	3 13/16	3	9.21
CLGRP50	2	13.3	1 1/4	7 11/16	3 3/8	3 1/16	5 29/32	4 7/16	3 11/32	13.3
CLGRP56	2 1/4	17.1	1 1/4	8 3/8	3 27/32	3 3/16	6 3/8	4 9/16	3 15/16	17.1
CLGRP64	2 1/2	19.0	1 1/4	8 15/16	4 1/8	3 7/16	6 5/8	4 11/16	4 7/16	19.0
CLGRP69	2 3/4	22.4	1 1/4	9 9/16	4 13/32	3 19/32	6 27/32	5	4 7/16	22.4
CLGRP75	3	28.0	1 1/2	10 21/32	4 3/4	3 27/32	7 5/8	5 5/16	5 11/32	28.0



# Green Pin® Wire Rope Clip

## Technical drawing

