



Green Pin® Closed Spelter Socket

Green Pin® Closed Spelter Socket



Highlights

- ✓ High tensile steel
- ✓ Galvanization assures long-term durability
- ✓ Superior stock availability of 99%
- ✓ Reliable Green Pin® quality and support

Description

The Green Pin® Closed Spelter Socket is made from high tensile steel. Its long-term durability is assured due to galvanization. The Green Pin® Closed Spelter Socket is available for a diameter wire rope of 6-7 up to 120-130 mm.

Product details

Productcode	G-6411
Material	high tensile steel
Finish	hot dipped galvanized
Certification	2.1 2.2 3.1 CE

www.greenpin.com



Green Pin® Closed Spelter Socket

Technical specifications in millimeters

Article code	Number	minimum breaking load	diameter wire rope	A length	B width	C width inside bow	D length inside bow	E thickness bow	F thickness bow	G opening	Net weight (kg)
SKGCS007	296	8	6 - 7	101	37	22	40	11	13	9	0.26
SKGCS010	297	12	8 - 10	119	43	25	48	14	17,5	12	0.50
SKGCS013	298	20	11 - 13	140	52	30	58	18	23,5	15	0.72
SKGCS016	299	25	14 - 16	162	68	37	66	21	26	17,5	1.47
SKGCS018	200	45	18 - 19	194	76	42	78	27	32	21,5	2.24
SKGCS022	201	70	20 - 22	224	92	47	90	33	38	24	4.20
SKGCS025	204	85	23 - 26	253	104	57	103	36	44	28	6.03
SKGCS028	207	105	27 - 30	282	114	63	116	39	51	32	7.85
SKGCS032	212	136	31 - 36	312	127	70	130	43	57	38	10.8
SKGCS038	215	150	37 - 39	358	136	79	155	51	63	41	13.6
SKGCS042	217	170	40 - 42	390	146	83	171	54	70	44	17.0
SKGCS045	219	225	43 - 48	443	171	93	198	55	76	51	26



Green Pin® Closed Spelter Socket

Technical specifications in millimeters

Article code	Number	minimum breaking load	diameter wire rope	A length	B width	C width inside bow	D length inside bow	E thickness bow	F thickness bow	G opening	Net weight (kg)
SKGCS054	222	280	49 - 54	502	193	100	224	62	82	57	37.5
SKGCS057	224	360	55 - 60	548	216	112	247	73	92	63	54.5
SKGCS064	226	425	61 - 68	597	241	140	270	79	102	73	69.5
SKGCS073	227	460	69 - 75	644	273	159	286	79	124	79	100
SKGCS075	228	560	76 - 80	686	292	171	298	83	133	86	121
SKGCS085	229	625	81 - 86	743	311	184	311	102	146	92	156
SKGCS090	230	720	87 - 93	788	330	197	330	102	159	99	181
SKGCS100	231	875	94 - 102	845	362	216	356	108	178	108	210
SKGCS110	233	1200	108 - 115	1000	405	235	425	125	190	125	334
SKGCS120	240	1300	120 - 130	1150	450	260	525	125	200	143	500

www.greenpin.com



Green Pin® Closed Spelter Socket

Technical specifications in inches

Article code	Number	minimum breaking load	diameter wire rope (inch)	A length (inch)	B width (inch)	C width inside bow (inch)	D length inside bow (inch)	E thickness bow (inch)	F thickness bow (inch)	G opening (inch)	Net weight (LBS)
SKGCS007	296	8	1/4	3 31/32	1 15/32	7/8	1 19/16	7/16	1/2	11/32	0.56
SKGCS010	297	12	3/8	4 11/16	1 11/16	31/32	1 7/8	9/16	11/16	15/32	1.10
SKGCS013	298	20	7/16 - 1/2	5 1/2	2 1/16	1 3/16	2 9/32	23/32	15/16	19/32	1.59
SKGCS016	299	25	9/16 - 5/8	6 3/8	2 11/16	1 15/32	2 19/32	13/16	1 1/32	11/16	3.24
SKGCS018	200	45	3/4	7 5/8	3	1 21/32	3 1/16	1 1/16	1 1/4	27/32	4.94
SKGCS022	201	70	7/8	8 13/16	3 5/8	1 27/32	3 17/32	1 5/16	1 1/2	15/16	9.27
SKGCS025	204	85	1	9 31/32	4 3/32	2 1/4	4 1/16	1 13/32	1 23/32	1 3/32	13.3
SKGCS028	207	105	1 1/8	11 3/32	4 1/2	2 15/32	4 9/16	1 17/32	2	1 1/4	17.3
SKGCS032	212	136	1 1/4 - 1 3/8	12 9/32	5	2 3/4	5 1/8	1 11/16	2 1/4	1 1/2	23.7
SKGCS038	215	150	1 1/2	14 3/32	5 11/32	3 1/8	6 3/32	2	2 15/32	1 5/8	30.0
SKGCS042	217	170	1 5/8	15 11/32	5 3/4	3 9/32	6 23/32	2 1/8	2 3/4	1 23/32	37.5
SKGCS045	219	225	1 3/4 - 1 7/8	17 7/16	6 23/32	3 21/32	7 25/32	2 5/32	3	2	57.3



Green Pin® Closed Spelter Socket

Technical specifications in inches

Article code	Number	minimum breaking load	diameter wire rope (inch)	A length (inch)	B width (inch)	C width inside bow (inch)	D length inside bow (inch)	E thickness bow (inch)	F thickness bow (inch)	G opening (inch)	Net weight (LBS)
SKGCS054	222	280	2 - 2 1/8	19 3/4	7 19/32	3 15/16	8 13/16	2 7/16	3 7/32	2 1/4	82.7
SKGCS057	224	360	2 1/4 - 2 3/8	21 9/16	8 1/2	4 13/32	9 23/32	2 7/8	3 5/8	2 15/32	120
SKGCS064	226	425	2 1/2 - 2 5/8	23 1/2	9 1/2	5 1/2	10 5/8	3 1/8	4 1/32	2 7/8	153
SKGCS073	227	460	2 3/4 - 2 7/8	25 11/32	10 3/4	6 1/4	11 1/4	3 1/8	4 7/8	3 1/8	221
SKGCS075	228	560	3 - 3 1/8	27	11 1/2	6 23/32	11 23/32	3 9/32	5 1/4	3 3/8	266
SKGCS085	229	625	3 1/4 - 3 3/8	29 1/4	12 1/4	7 1/4	12 1/4	4 1/32	5 3/4	3 5/8	344
SKGCS090	230	720	3 1/2 - 3 5/8	31 1/32	13	7 3/4	13	4 1/32	6 1/4	3 29/32	399
SKGCS100	231	875	3 3/4 - 4	33 9/32	14 1/4	8 1/2	14 1/32	4 1/4	7	4 1/4	463
SKGCS110	233	1200	4 1/4 - 4 1/2	39 3/8	15 15/16	9 1/4	16 23/32	4 29/32	7 15/32	4 29/32	736
SKGCS120	240	1300	4 3/4 - 5	45 9/32	17 23/32	10 1/4	20 21/32	4 29/32	7 7/8	5 5/8	1103

www.greenpin.com



Green Pin[®] Closed Spelter Socket

Technical drawing

