



Green Pin® Open Spelter Socket BN

Open spelter socket with safety bolt



Highlights

- ✓ Double safety (cotter pin & safety bolt)
- ✓ High tensile steel
- ✓ Galvanization assures long-term durability
- ✓ Superior stock availability of 99%
- ✓ Reliable Green Pin® quality and support

Description

The Green Pin® Open Spelter Socket BN is an open spelter socket with a safety bolt. The socket offers a double safety (split pin and safety bolt) which prevents accidental unscrewing of the pin. The socket is made from high tensile steel, while galvanization ensures its long-term durability. The Green Pin® Open Spelter Socket BN is available for wire rope with a diameter from 6-7 up to 40-42 mm.

Product details

Productcode	G-6422
Material	high tensile steel
Finish	hot dipped galvanized
Certification	2.1 2.2 3.1 CE

www.greenpin.com



Green Pin® Open Spelter Socket BN

Technical specifications in millimeters

Article code	Number	minimum breaking load	diameter wire rope	A length	B width	C width inside	D diameter pin	E length inside	F opening	Net weight (kg)
SKGOS007SB	196	8	6 - 7	109	69	19	16	33	9	0.40
SKGOS010SB	197	12	8 - 10	124	83	21	20	35	12	0.80
SKGOS013SB	198	20	11 - 13	143	101	26	25	37	15	1.30
SKGOS016SB	199	25	14 - 16	172	124	33	30	49	18	2.32
SKGOS018SB	100	45	18 - 19	205	138	38	35	58	21	3.81
SKGOS022SB	104	60	20 - 22	235	148	44	41	68	24	5.56
SKGOS025SB	108	85	23 - 26	275	176	51	50	76	28	9.90
SKGOS028SB	111	105	27 - 30	306	193	57	57	85	32	13.8
SKGOS032SB	115	136	31 - 36	338	210	63	63	95	38	18.4
SKGOS038SB	118	150	37 - 39	394	230	76	70	127	41	26.9
SKGOS042SB	120	170	40 - 42	418	244	76	77	126	44	32



Green Pin® Open Spelter Socket BN

Technical specifications in inches

Article code	Number	minimum breaking load	diameter wire rope (inch)	A length (inch)	B width (inch)	C width inside (inch)	D diameter pin (inch)	E length inside (inch)	F opening (inch)	Net weight (LBS)
SKGOS007SB	196	8	1/4	4 9/32	2 23/32	3/4	5/8	1 5/16	11/32	0.88
SKGOS010SB	197	12	3/8	4 7/8	3 9/32	13/16	25/32	1 3/8	15/32	1.76
SKGOS013SB	198	20	7/16 - 1/2	5 5/8	3 31/32	1 1/32	31/32	1 15/32	19/32	2.86
SKGOS016SB	199	25	9/16 - 5/8	6 25/32	4 7/8	1 5/16	1 3/16	1 15/16	23/32	5.12
SKGOS018SB	100	45	3/4	8 1/16	5 7/16	1 1/2	1 3/8	2 9/32	13/16	8.40
SKGOS022SB	104	60	7/8	9 1/4	5 13/16	1 23/32	1 5/8	2 11/16	15/16	12.3
SKGOS025SB	108	85	1	10 13/16	6 15/16	2	1 31/32	3	1 3/32	21.8
SKGOS028SB	111	105	1 1/8	12 1/16	7 19/32	2 1/4	2 1/4	3 11/32	1 1/4	30.3
SKGOS032SB	115	136	1 1/4 - 1 3/8	13 5/16	8 9/32	2 15/32	2 15/32	3 3/4	1 1/2	40.5
SKGOS038SB	118	150	1 1/2	15 1/2	9 1/16	3	2 3/4	5	1 5/8	59.3
SKGOS042SB	120	170	1 5/8	16 15/32	9 19/32	3	3 1/32	4 31/32	1 23/32	70.6



Green Pin® Open Spelter Socket BN

Technical drawing

