



## Green Pin<sup>®</sup> Connecting Link EN1677-1

Grade 8 connecting link EN1677-1



### Highlights

- ✓ Reliable Green Pin<sup>®</sup> quality and support
- ✓ Superior stock availability of 99%

### Description

The Green Pin<sup>®</sup> Connecting Link EN1677-1 is a grade 8 connecting link according to European standard for components for sling EN 1677-1. These connectors provide fast, easy assembly by using just a hammer. It is designed to connect eye and eye swivel hooks and master links to grade 8 chains all together. The spring bush ensures that the pin stays secured in place within the two halves of the connecting link. The Green Pin<sup>®</sup> Connecting Link EN1677-1 is available in a range to suit 6 mm up to 32 mm grade 8 chain.

### Product details

<b>Productcode</b>	MJ
<b>Material</b>	alloy steel, Grade 8, quenched and tempered
<b>Safety factor</b>	MBL equals 4 x WLL
<b>Finish</b>	painted white
<b>Certification</b>	<b>2.1 2.2 3.1 MTCa MPIb DGUV</b>
<b>Standard</b>	EN 1677-1

[www.greenpin.com](http://www.greenpin.com)



## Green Pin® Connecting Link EN1677-1

### Technical specifications in millimeters

Article code	working load limit	for chain diameter	Net weight	A diameter	B width outside	C width inside	D length inside	E length inside	F diameter eye	G width inside	Net weight (kg)
GPMJ6	1,12	6	0.09	8	42	11	20	52	11	15	0.09
GPMJ7/8	2	7 - 8	0.15	9	53	14	20	55	13	19	0.15
GPMJ10	3,2	10	0.28	10	66	18	23	64	18	23	0.28
GPMJ13	5,4	13	0.64	14	83	21	32	85	24	28	0.64
GPMJ16	8,2	16	1.16	17	103	25	40	105	28	34	1.16
GPMJ18/20	12,8	18 - 20	1.95	21	120	33	50	129	33	42	1.95
GPMJ22	15,5	22	2.94	23	143	40	55	140	37	51	2.94
GPMJ26	21,6	26	4.12	26	169	45	60	153	46	57	4.12
GPMJ32	32,8	32	8.30	39	197	52	68	174	56	67	8.30



## Green Pin® Connecting Link EN1677-1

### Technical specifications in inches

Article code	working load limit	for chain diameter (inch)	Net weight	A diameter (inch)	B width outside (inch)	C width inside (inch)	D length inside (inch)	E length inside (inch)	F diameter eye (inch)	G width inside (inch)	Net weight (LBS)
GPMJ6	1,12	7/32	0.20	5/16	1 21/32	7/16	25/32	2 2/16	7/16	19/32	0.20
GPMJ7/8	2	1/4"-5/16	0.33	11/32	2 3/32	9/16	25/32	2 5/32	1/2	3/4	0.33
GPMJ10	3,2	3/8	0.62	13/32	2 19/32	23/32	29/32	2 17/32	23/32	29/32	0.62
GPMJ13	5,4	1/2	1.40	9/16	3 9/32	13/16	1 1/4	3 11/32	15/16	1 3/32	1.40
GPMJ16	8,2	5/8	2.56	21/32	4 1/16	31/32	1 9/16	4 1/8	1 3/32	1 11/32	2.56
GPMJ18/20	12,8	3/4	4.31	13/16	4 23/32	1 5/16	1 31/32	5 3/32	1 5/16	1 21/32	4.31
GPMJ22	15,5	7/8	6.49	29/32	5 5/8	1 9/16	2 5/32	5 1/2	1 15/32	2	6.49
GPMJ26	21,6	1	9.09	1 1/32	6 5/16	1 25/32	2 3/8	6 1/32	1 13/16	2 1/4	9.09
GPMJ32	32,8	1 1/4	18.3	1 17/32	7 3/4	2 2/16	2 11/16	6 27/32	2 7/32	2 5/8	18.3



Green Pin<sup>®</sup> Connecting Link EN1677-1

Technical drawing

