



Green Pin[®] Small Lifting Eye

Grade 8 small lifting eye



Highlights

- ✓ Reliable Green Pin[®] quality and support
- ✓ Superior stock availability of 99%

Description

The Green Pin[®] Small Lifting Eye is a grade 8 small lifting eye. These small lifting eyes are designed for assembly with all Green Pin[®] clevis components. These combinations result in articulated lifting eyes, capable of lifting angles. Fitting the lifting eyes is made easier with their 6 sided bases. The minimum safety factor is 5:1. The Green Pin[®] Small Lifting Eye is available in a range with a working load limit from 0.5 t. up to 15 t.

Product details

Productcode	OL
Material	alloy steel, Grade 8, quenched and tempered
Safety factor	MBL equals 4 x WLL
Finish	painted white
Certification	2.1 2.2 MTCa MPIb CE

www.greenpin.com



Green Pin® Small Lifting Eye

Technical specifications in millimeters

Article code	working load limit	A diameter thread	B diameter base	C diameter eye inside	D length	E thickness base	F width	Net weight (kg)
GPOL8	0,5	8	28	8	30	13	6	0.05
GPOL10	0,9	10	28	8	30	13	6	0.06
GPOL12	1,25	12	28	8	30	13	6	0.06
GPOL14	1,5	14	31	9	45	18	9	0.12
GPOL16	1,9	16	31	9	45	18	9	0.14
GPOL18	2,25	18	31	9	45	18	9	0.15
GPOL20	3,12	20	40	13	55	20	10	0.25
GPOL22	3,8	22	40	13	55	20	10	0.28
GPOL24	5	24	53	16	68	29	12	0.53
GPOL27	6,25	27	53	16	68	29	12	0.58
GPOL30	8	30	59	20	90	35	13	0.94
GPOL33	9	30	59	20	90	35	13	1.03



Green Pin® Small Lifting Eye

Technical specifications in millimeters

Article code	working load limit	A diameter thread	B diameter base	C diameter eye inside	D length	E thickness base	F width	Net weight (kg)
GPOL36	10	36	59	20	90	35	13	1.12
GPOL39	12,5	39	75	24	105	40	18	1.90
GPOL42	15	42	75	24	105	40	18	2.02

www.greenpin.com



Green Pin® Small Lifting Eye

Technical specifications in inches

Article code	working load limit	A diameter thread (inch)	B diameter base (inch)	C diameter eye inside (inch)	D length (inch)	E thickness (inch)	F width (inch)	Net weight (LBS)
GPOL8	0,5	5/16	1 3/32	5/16	1 3/16	1/2	1/4	0.12
GPOL10	0,9	13/32	1 3/32	5/16	1 3/16	1/2	1/4	0.12
GPOL12	1,25	15/32	1 3/32	5/16	1 3/16	1/2	1/4	0.14
GPOL14	1,5	9/16	1 7/32	11/32	1 25/32	23/32	11/32	0.27
GPOL16	1,9	5/8	1 7/32	11/32	1 25/32	23/32	11/32	0.31
GPOL18	2,25	23/32	1 7/32	11/32	1 25/32	23/32	11/32	0.33
GPOL20	3,12	25/32	1 9/16	1/2	2 5/32	25/32	13/32	0.55
GPOL22	3,8	7/8	1 9/16	1/2	2 5/32	25/32	13/32	0.62
GPOL24	5	15/16	2 3/32	5/8	2 11/16	1 5/32	15/32	1.17
GPOL27	6,25	1 1/16	2 1/8	5/8	2 11/16	1 3/32	15/32	1.28
GPOL30	8	1 3/16	2 5/16	25/32	3 17/32	1 3/8	1/2	2.07
GPOL33	9	1 5/16	2 5/16	25/32	3 17/32	1 3/8	1/2	2.27



Green Pin® Small Lifting Eye

Technical specifications in inches

Article code	working load limit	A diameter thread (inch)	B diameter base (inch)	C diameter eye inside (inch)	D length (inch)	E thickness (inch)	F width (inch)	Net weight (LBS)
GPOL36	10	1 13/32	2 5/16	25/32	3 17/32	1 3/8	1/2	2.47
GPOL39	12,5	1 17/32	2 15/16	15/16	4 1/8	1 9/16	23/32	4.19
GPOL42	15	1 21/32	2 15/16	15/16	4 1/8	1 9/16	23/32	4.45

www.greenpin.com



Green Pin® Small Lifting Eye

Technical drawing

