



Green Pin® Sling Hook CL GR10

Grade 10 clevis sling hook



Highlights

- ✓ Reliable Green Pin® quality and support
- ✓ Superior stock availability of 99%

Description

The Green Pin® Sling Hook CL is a grade 10 clevis sling hook. The sling hook can be used for general lifting applications. It can be quickly connected to the load lifting points thanks to its easy operating latch, which guarantees full safety. To connect simply push the latch, connect the hook to the lifting point, and release the latch. The forged latch guarantees a longer lifespan. It strongly limits the risk that the operator uses the hook without latch. The latch is fitted with a stainless steel spring and a sturdy pin. The clevis design enables a direct connection to grade 10 chain. The Green Pin® Sling Hook CL is available in a range to suit 6 mm up to 20 mm grade 10 chain.

Product details

Productcode	UCSC
Material	alloy steel, Grade 10, quenched and tempered
Safety factor	MBL equals 4 x WLL
Finish	painted blue
Certification	2.1 2.2 3.1 MTCa MPIb DGUV



Green Pin® Sling Hook CL GR10

Technical specifications in millimeters

Article code	working load limit	for chain diameter	A length	B width	C opening hook	D thickness	E width	F width outside	G width outside	H length outside	I diameter pin	Net weight (kg)
GPUCSC6	1,4	6	74	7	26	15	20	28	72	108	8	0.29
GPUCSC7	1,95	7	95	9	30	20	24	32	87	136	9	0.58
GPUCSC8	2,6	8	95	9	30	20	24	32	87	136	9	0.58
GPUCSC10	4	10	113	11	33	24	29	42	106	164	13	1.11
GPUCSC13	6,8	13	139	15	37	32	39	54	133	208	16	2.12
GPUCSC16	10,3	16	162	18	44	40	44	68	165	240	20	3.78
GPUCSC20	16	20	199	23	61	49	62	82	208	305	24	7.49

www.greenpin.com



Green Pin® Sling Hook CL GR10

Technical specifications in inches

Article code	working load limit	for chain diameter (inch)	A length (inch)	B width (inch)	C opening hook (inch)	D thickness (inch)	E width (inch)	F width outside (inch)	G width outside (inch)	H length outside (inch)	I diameter pin (inch)	Net weight (LBS)
GPUCSC6	1,4	7/32	2 29/32	9/32	1 1/32	19/32	25/32	1 3/32	2 27/32	4 1/4	5/16	0.64
GPUCSC7	1,95	9/32	3 3/4	11/32	1 3/16	25/32	15/16	1 1/4	3 7/16	5 11/32	13/32	1.29
GPUCSC8	2,6	5/16	3 3/4	11/32	1 3/16	25/32	15/16	1 1/4	3 7/16	5 11/32	11/32	1.29
GPUCSC10	4	3/8	4 7/16	15/32	1 5/16	15/16	1 5/32	1 21/32	4 3/16	6 15/32	1/2	2.45
GPUCSC13	6,8	1/2	5 15/32	19/32	1 15/32	1 1/4	1 17/32	2 1/8	5 1/4	8 3/16	5/8	4.68
GPUCSC16	10,3	5/8	6 3/8	3/4	1 23/32	1 9/16	1 23/32	2 11/16	6 1/2	9 7/16	25/32	8.34
GPUCSC20	16	3/4	7 27/32	29/32	2 13/32	1 15/16	2 7/16	3 7/32	8 3/16	12	15/16	16.5

www.greenpin.com



Green Pin® Sling Hook CL GR10

Technical drawing

