



Green Pin® Sling Hook E

Grade 10 eye sling hook



Highlights

- ✓ Superior stock availability of 99%
- ✓ Reliable Green Pin® quality and support

Description

The Green Pin® Sling Hook E is a grade 10 eye sling hook. The sling hook can be used for general lifting applications. It can be quickly connected to the load lifting points thanks to its easy operating latch, which guarantees full safety. To connect simply push the latch, connect the hook to the lifting point, and release the latch. The forged latch guarantees a longer lifespan. It strongly limits the risk that the operator uses the hook without latch. The latch is fitted with a stainless steel spring and a sturdy pin. The eye of the hook can be connected to grade 10 chain with a connecting link or an omega link, to a webbing with a web sling connector or to a wire rope with a thimble. The flat on the eye enables the assembly with an omega link or on a thimble. The Green Pin® Sling Hook E is available in a range to suit 6 mm up to 20 mm grade 10 chain.

Product details

Productcode	UCSO
Material	alloy steel, Grade 10, quenched and tempered
Safety factor	MBL equals 4 x WLL
Finish	painted blue
Certification	2.1 2.2 3.1 MTCa MPIb DGUV
Note	from 10 t without flat part



Green Pin® Sling Hook E

Technical specifications in millimeters

Article code	working load limit	for chain diameter	A length	B diameter eye inside	C opening hook	D thickness	E width	F diameter eye outside	G width outside	H length	I width	J thickness	Net weight (kg)
GPUCSO6	1,4	6	86	23	26	15	19	43	73	114	10	6	0.28
GPUCSO8	2,6	8	103	26	30	19	24	51	87	139	12	8	0.52
GPUCSO10	4	10	129	36	33	24	28	65	106	171	15	10	1.09
GPUCSO13	6,8	13	152	41	37	32	39	77	133	209	18	12	1.94
GPUCSO16	10,3	16	191	52	43	40	43	94	165	255	21	17	3.51
GPUCSO20	16	20	237	61	61	49	61	115	208	326	28	21	7.08

www.greenpin.com



Green Pin® Sling Hook E

Technical specifications in inches

Article code	working load limit	for chain diameter (inch)	A length (inch)	B diameter eye inside (inch)	C opening hook (inch)	D thickness (inch)	E width (inch)	F diameter eye outside (inch)	G width outside (inch)	H length (inch)	I width (inch)	J thickness (inch)	Net weight (LBS)
GPUCSO6	1,4	7/32	3 5/16	29/32	1 1/32	19/32	3/4	1 11/16	2 27/32	4 1/2	13/32	1/4	0.63
GPUCSO8	2,6	5/16	4 1/16	1 1/32	1 3/16	25/32	15/16	2	3 7/16	5 15/32	15/32	5/16	1.14
GPUCSO10	4	3/8	5 3/32	1 13/32	1 5/16	15/16	1 3/32	2 9/16	4 3/16	6 23/32	19/32	13/32	2.40
GPUCSO13	6,8	1/2	5 31/32	1 5/8	1 15/32	1 1/4	1 17/32	3 1/32	5 1/4	8 7/32	23/32	15/32	4.28
GPUCSO16	10,3	5/8	7 17/32	2 1/16	1 11/16	1 9/16	1 11/16	3 11/16	6 1/2	10 1/32	13/16	5/8	7.74
GPUCSO20	16	3/4	9 11/32	2 13/32	2 13/32	1 15/16	2 13/32	4 17/32	8 3/16	12 27/32	1 3/32	13/16	15.6

www.greenpin.com



Green Pin® Sling Hook E

Technical drawing

