PETROLEUM HOSE



4414

NITRILE PETROLEUM SUCTION HOSE - 300 PSI







CONSTRUCTION: Tube nitrile, smooth and black.

ARPM Class A. Cover is CR, ARPM Class B. Reinforcement is two-ply synthetic fabric with a dual wire helix.

TEMPERATURE: -25°F (-32°C) to +200°F (+93°C)

BRANDING: Jason logo 4414 PETROLEUM SUCTION

WP 300 PSI 20.70 BAR. Red mylar longitudinal stripe. **APPLICATION:** For the transfer of petroleum products,

including gasoline under pressure and

gravity flow.

FEATURES:

- HD construction that handles up to 300 PSI applications
- Cover is resistant to weathering and abrasion
- Heat and ozone resistant
- All sizes are full vacuum

SAFETY FACTOR: 3:1

Part Number	I.D.		O.D.		Reinf.	Max W.P. @ 68°F		Vacuum @ 68°F	Weight		Minimum Bend Radius		Std. Length
	in.	mm	in.	mm	Plies	PSI	BAR	@ 08°F	lb./ft.	KG/m	in.	mm	(ft.)
4414-0100-100	1	25.40	1.46	37.08	2	300	20.70	29.0	0.53	0.79	3.50	88.90	100
4414-0125-100	1-1/4	31.75	1.73	43.94	2	300	20.70	29.0	0.70	1.04	4.00	101.60	100
4414-0150-100	1-1/2	38.10	2.00	50.80	2	300	20.70	29.0	0.92	1.37	5.00	127.00	100
4414-0200-100	2	50.80	2.50	63.50	2	300	20.70	29.0	1.27	1.89	8.00	203.20	100
4414-0200-200	2	50.80	2.50	63.50	2	300	20.70	29.0	1.27	1.89	8.00	203.20	200
4414-0250-100	2-1/2	63.50	3.11	78.99	2	300	20.70	29.0	1.66	2.47	10.00	254.00	100
4414-0300-100	3	76.20	3.62	91.95	2	300	20.70	29.0	2.19	3.26	12.00	304.80	100
4414-0300-200	3	76.20	3.62	91.95	2	300	20.70	29.0	2.19	3.26	12.00	304.80	200
4414-0400-100	4	101.60	4.65	118.11	2	300	20.70	29.0	2.89	4.30	17.00	431.80	100
4414-0400-200	4	101.60	4.65	118.11	2	300	20.70	29.0	2.89	4.30	17.00	431.80	200
4414-0600-100	6	152.40	6.91	175.51	2	300	20.70	29.0	6.47	9.96	27.00	685.80	100
4414-0800-020	8	203.20	8.98	228.00	2	300	20.70	29.0	6.92	10.30	48.00	1219.20	20

Working pressure (W.P.) is temperature dependent. See the General Information section Table II - Pressure Re-Rating for increased Temperatures (Page 10) for more information.