



## Green Pin® Self Locking Hook E

Grade 10 eye self locking hook



### Highlights

- ✓ Reliable Green Pin® quality and support
- ✓ Superior stock availability of 99%

### Description

The Green Pin® Self-Locking Hook E is a grade 10 eye self-locking hook. The self-locking hook locks automatically as soon as it is brought under tension. To release the load the user must manually unlock the hook, which prevents unintended release. This hook brings a full safety for lifting as the latch cannot be removed. The eye of the hook can be connected to grade 10 chain with a connecting link, to a webbing with a web sling connector or to a wire rope with a thimble. The flat on the eye enables the assembly with an omega link or on a thimble. The Green Pin® Self-Locking Hook E is available in a range to suit 6 mm up to 20 mm grade 10 chain.

### Product details

|                      |                                              |
|----------------------|----------------------------------------------|
| <b>Productcode</b>   | UXLO                                         |
| <b>Material</b>      | alloy steel, Grade 10, quenched and tempered |
| <b>Safety factor</b> | MBL equals 4 x WLL                           |
| <b>Finish</b>        | painted blue                                 |
| <b>Certification</b> | <b>2.1 2.2 3.1 MTCa MPIb DGUV</b>            |

[www.greenpin.com](http://www.greenpin.com)



Green Pin® Self Locking Hook E

Technical specifications in millimeters

| Article code | working load limit | for chain diameter | A length | B diameter eye inside | C opening hook | D thickness | E width | F width outside | G width outside | H length | I width | J thickness | Net weight<br>(kg) |
|--------------|--------------------|--------------------|----------|-----------------------|----------------|-------------|---------|-----------------|-----------------|----------|---------|-------------|--------------------|
| GPUXLO0      | 1,4                | 6                  | 113      | 24                    | 32             | 16          | 24      | 47              | 75              | 148      | 11      | 6           | 0.51               |
| GPUXLO1      | 2,6                | 8                  | 136      | 30                    | 43             | 24          | 28      | 57              | 91              | 178      | 14      | 8           | 0.91               |
| GPUXLO2      | 4                  | 10                 | 168      | 36                    | 48             | 32          | 34      | 68              | 110             | 218      | 16      | 10          | 1.79               |
| GPUXLO3      | 6,8                | 13                 | 201      | 47                    | 63             | 37          | 43      | 87              | 141             | 264      | 20      | 13          | 3.36               |
| GPUXLO4      | 10,3               | 16                 | 251      | 60                    | 75             | 43          | 56      | 111             | 182             | 332      | 26      | 16          | 7.00               |
| GPUXLO5      | 16                 | 20                 | 283      | 70                    | 90             | 52          | 62      | 126             | 203             | 373      | 28      | 21          | 9.22               |

[www.greenpin.com](http://www.greenpin.com)



## Green Pin® Self Locking Hook E

### Technical specifications in inches

| Article code | working load limit | for chain diameter (inch) | A length (inch) | B diameter eye inside (inch) | C opening hook (inch) | D thickness (inch) | E width (inch) | F width outside (inch) | G width outside (inch) | H length (inch) | I width (inch) | J thickness (inch) | Net weight (LBS) |
|--------------|--------------------|---------------------------|-----------------|------------------------------|-----------------------|--------------------|----------------|------------------------|------------------------|-----------------|----------------|--------------------|------------------|
| GPUXLO0      | 1,4                | 7/32                      | 4 7/16          | 15/16                        | 1 1/4                 | 5/8                | 15/16          | 1 27/32                | 2 15/16                | 5 13/16         | 7/16           | 1/4                | 1.13             |
| GPUXLO1      | 2,6                | 5/16                      | 5 11/32         | 1 3/16                       | 1 11/16               | 15/16              | 1 3/32         | 2 1/4                  | 3 19/32                | 7               | 9/16           | 5/16               | 2.01             |
| GPUXLO2      | 4                  | 3/8                       | 6 5/8           | 1 13/32                      | 1 7/8                 | 1 1/4              | 1 11/32        | 2 11/16                | 4 11/32                | 8 19/32         | 5/8            | 13/32              | 3.95             |
| GPUXLO3      | 6,8                | 1/2                       | 7 29/32         | 1 27/32                      | 2 15/32               | 1 15/32            | 1 11/16        | 3 7/16                 | 5 9/16                 | 10 13/32        | 25/32          | 1/2                | 7.41             |
| GPUXLO4      | 10,3               | 5/8                       | 9 7/8           | 2 3/8                        | 2 15/16               | 1 11/16            | 2 7/32         | 4 3/8                  | 7 5/32                 | 13 1/16         | 1 1/32         | 5/8                | 15.4             |
| GPUXLO5      | 16                 | 3/4                       | 11 5/32         | 2 3/4                        | 3 17/32               | 2 1/16             | 2 7/16         | 4 31/32                | 8                      | 14 11/16        | 1 3/32         | 13/16              | 20.3             |

[www.greenpin.com](http://www.greenpin.com)



## Green Pin® Self Locking Hook E

Technical drawing

