

# CRIMP COUPLINGS, FERRULES & SLEEVES

## CAM & GROOVE CRIMP COUPLINGS

All Cam & Groove Fittings are Aluminum

### PART C FEMALE COUPLER x HOSE SHANK

Female end fits male adapter or Dust Plug. Shank fits into hose ID. Bowl has recess for washer replacement.



Part Number	Size (inch)	Shank O.D.		Serrations	Stem O.D.	
		inch	mm		inch	mm
<b>C150AC</b>	1-1/2	1.535	39.0	10	1.54	39.0
<b>C200AC</b>	2	2.027	51.5	12	2.03	51.5
<b>C250AC</b>	2-1/2	2.527	64.2	15	2.53	64.2
<b>C300AC</b>	3	3.031	77.0	14	3.03	77.0
<b>C400AC</b>	4	4.035	102.5	15	4.04	102.5
<b>C600AC</b>	6	6.047	153.6	22	6.05	153.6

**WARNING:** This product can expose you to chemicals including carbon black, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information visit [www.P65WARNINGS.ca.gov](http://www.P65WARNINGS.ca.gov)

### PART E MALE ADAPTER x HOSE SHANK

Male end fits female coupler or Dust Cap. Shank fits into hose ID.



Part Number	Size (inch)	Shank O.D.		Serrations	Stem O.D.	
		inch	mm		inch	mm
<b>E150AC</b>	1-1/2	1.535	39.0	10	1.54	39.0
<b>E200AC</b>	2	2.027	51.5	12	2.03	51.5
<b>E250AC</b>	2-1/2	2.527	64.2	15	2.53	64.2
<b>E300AC</b>	3	3.031	77.0	14	3.03	77.0
<b>E400AC</b>	4	4.035	102.5	15	4.04	102.5
<b>E600AC</b>	6	6.047	153.6	22	6.05	153.6

## COMBINATION HOSE NIPPLES MALE x HOSE SHANK-PLATED STEEL

Combination Nipples are used in a variety of fluid applications. End (male) threads are NPT  
Will mate with Foot Valves, Strainers, Cam & Groove Part A & D, etc. and are the same size as the shank.



Part Number	Size (inch)	Stem O.D.	
		inch	mm
<b>CN150PC</b>	1-1/2	1.54	39.0
<b>CN200PC</b>	2	2.03	51.5
<b>CN250PC</b>	2-1/2	2.53	64.2
<b>CN300PC</b>	3	3.03	77.0
<b>CN400PC</b>	4	4.04	102.5
<b>CN600PC</b>	6	6.05	153.6