

## **MATERIAL HANDLING HOSE**

4322 1/8" TUBE SAND & DRY CEMENT, POWDER DISCHARGE HOSE 4323 3/16" TUBE SAND & DRY CEMENT, POWDER DISCHARGE HOSE 4324 1/4" TUBE SAND & DRY CEMENT, POWDER DISCHARGE HOSE







CONSTRUCTION: Tube is NR/SBR blend, black and

static-dissipating. Reinforcement is

a two-ply synthetic fabric.

**TEMPERATURE:** -40°F (-40°C) to +185°F (+85°C)

**BRANDING:** Jason logo 4322, 4323 or 4324 DRY

BULK DISCHARGE ID Tube WP 75 PSI

5.17 BAR.

White mylar longitudinal stripe.

**APPLICATION:** For pneumatic discharge of dry powders,

dry cement or other dry materials. Also used for sand/water mix applications on

fracking sites.

## **FEATURES:**

- Special static dissipating tube compound
- Weather and ozone resistant
- High abrasion resistant tube resists cutting/gouging
- Can be rolled for transport and storage

**SAFETY FACTOR: 3:1** 

Part Number	I.D.		O.D.		Reinf.	Max W.P. @ 68°F		Vacuum @ 68°F	Weight		Minimum Bend Radius		Std. Length
	in.	mm	in.	mm	Files	PSI	BAR	₩ 00 F	lb./ft.	KG/m	in.	mm	(ft.)
1/8" TUBE THICKNESS													
4322-0400-100	4	101.60	4.48	113.79	2	75	5.17	n/a	1.60	2.38	40.00	1016.00	100
4322-0500-100	5	127.00	5.46	138.68	2	75	5.17	n/a	1.88	2.80	50.00	1270.00	100
3/16" TUBE THICKNESS													
4323-0400-100	4	101.60	4.68	118.87	2	75	5.17	n/a	2.42	3.60	40.00	1016.00	100
4323-0500-100	5	127.00	5.68	144.27	2	75	5.17	n/a	2.92	4.35	50.00	1270.00	100
1/4" TUBE THICKNESS													
4324-0400-100	4	101.60	4.84	122.94	2	75	5.17	n/a	3.23	4.81	40.00	1016.00	100
4324-0500-100	5	127.00	5.84	148.34	2	75	5.17	n/a	3.80	5.65	50.00	1270.00	100

Working pressure (W.P.) is temperature dependent. See the General Information section Table II - Pressure Re-Rating for increased Temperatures (Page 10) for more information.