

WATER HOSE

4703 **HEAVY DUTY DJ MILL DISCHARGE HOSE & ASSEMBLIES**







CONSTRUCTION: Tube is SBR, smooth and black.

The cover is a double jacket made

with 100% polyester.

TEMPERATURE: -25°F (-32°C) to +185°F (+85°C)

BRANDING: Service Pressure 300 PSI.

APPLICATION: Municipal washdown or hydrant-to-truck

water supply line. Heavy duty equipment/ pump rental, ship/deck washdown.

FEATURES:

- Double cover gives heavy duty abrasion resistance
- Rolls flat for easy storage
- · Economical, lightweight and flexible
- Double cover increases service pressure rating

BULK HOSE

Part Number	I.D.		Coupling Bowl		Reinf. Plies	Service Pressure		Test Pressure		Vacuum @ 68°F	Weight		Std. Length
	in.	mm	in.	mm	Piles	PSI	BAR	PSI	BAR	@ 00 F	lb./ft.	KG/m	(ft.)
4703-1500	1-1/2	38.10	1.94	46.04	n/a	300	20.68	600	41.36	600	0.26	0.39	50
4703-2000	2	50.80	2.50	58.74	n/a	300	20.68	600	41.36	600	0.33	0.49	50
4703-2500	2-1/2	63.50	2.81	71.44	n/a	300	20.68	600	41.36	600	0.45	0.67	50
4703-1501	1-1/2	38.10	1.94	46.04	n/a	300	20.68	600	41.36	600	0.26	0.39	100
4703-2001	2	50.80	2.50	58.74	n/a	300	20.68	600	41.36	600	0.33	0.49	100
4703-2501	2-1/2	63.50	2.81	71.44	n/a	300	20.68	600	41.36	600	0.45	0.67	100

HOSE ASSEMBLIES CUT • COUPLED • COILED • TIED

All sizes may not be stocked in all locations. Check with customer service for availability.

Part	1.1	D.	Reinf.	Thread	Weight		Std. Length	
Number	in.	mm	Plies	Туре	lb./ft.	KG/m	(ft.)	
4703-1500-050ERNPS	1-1/2	38.10	n/a	NPS	15.00	22.32	50	
4703-1500-050ERNST	1-1/2	38.10	n/a	NST	15.00	22.32	50	
4703-2000-050ERNPS	2	50.80	n/a	NPS	20.00	29.76	50	
4703-2500-050ERNPS	2-1/2	63.50	n/a	NPS	25.00	37.20	50	
4703-2500-050ERNST	2-1/2	63.50	n/a	NST	25.00	37.20	50	

Couplings are internally expanded, aluminum, hardcoated NPS or NST Male x Female rocker lug

Note: Assembly is rated at 150 PSI. Service pressure is temperature dependent. See the General Information section Table II - Pressure Re-Rating for Increased Temperatures for more information.