



Green Pin® Round Web Sling Connecting Link

Grade 8 round web sling connecting link



Highlights

- ✓ Reliable Green Pin® quality and support
- ✓ Superior stock availability of 99%

Description

The Green Pin® Flat Web Sling Connecting Link is a grade 8 connecting link to be used with flat web sling. The flat half of this connecting link is designed to connect flat webbing slings directly to master links or to an eye hook, thanks to the other round half connecting link. The Green Pin® Flat Web Sling Connecting Link is available in a range to suit 2 t. up to 5.4 t. flat webbings.

Product details

Productcode	MJS
Material	alloy steel, Grade 8, quenched and tempered
Safety factor	MBL equals 4 x WLL
Finish	painted white
Certification	2.1 2.2 3.1 MTCa MPIb

www.greenpin.com



Green Pin® Round Web Sling Connecting Link

Technical specifications in millimeters

Article code	working load limit	for chain diameter	A diameter	B width outside	C width inside	D length inside	E length	F width inside	G diameter eye	H thickness	Net weight (kg)
GPMJS7/8	2	7 - 8	9	66	19	21	60	41	13	14	0.31
GPMJS10	3,2	10	10	75	23	24	75	46	18	15	0.51
GPMJS13	5,4	13	14	87	28	32	90	52	24	19	1.01

www.greenpin.com



Green Pin® Round Web Sling Connecting Link

Technical specifications in inches

Article code	working load limit	for chain diameter (inch)	A diameter (inch)	B width outside (inch)	C width inside (inch)	D length inside (inch)	E length (inch)	F width inside (inch)	G diameter eye (inch)	H thickness (inch)	Net weight (LBS)
GPMJS7/8	2	1/4 - 5/16	11/16	2 19/32	3/4	13/16	2 3/8	1 5/8	1/2	9/16	0.68
GPMJS10	3,2	3/8	13/32	2 15/16	29/32	15/16	2 15/16	3	23/32	19/32	1.13
GPMJS13	5,4	1/2	1 1/8	3 7/16	1 3/32	1 1/4	3 17/32	2 1/16	15/16	3/4	2.23

www.greenpin.com



Green Pin® Round Web Sling Connecting Link

Technical drawing

