


Green Pin® Hook E GR8

Grade 8 large eye hook with safety latch

- **Material:** alloy steel, grade 8
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** generally to EN 1677-2
- **Finish:** painted red
- **Certification:** 2.1 2.2 3.1



P-6714A



working load limit	length	diameter eye inside	opening hook	opening hook	thickness	width	diameter eye outside	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
1.25	81	19	24	20	16	19	37	0.3
1.6	91	22	26	22	18	22	45	0.44
2.5	105	27	32	27	20	27	52	0.63
3.2	124	32	34	30	24	31	62	1.27
5.4	147	39	44	37	31	36	74	1.76
8.2	190	50	55	48	37	48	96	3.6
12.8	230	64	64	53	48	61	126	7.7
16	254	70	70	60	58	69	139	10.8
22	316	89	91	77	63	81	169	16.7

In inch

working load limit	length	diameter eye inside	opening hook	opening hook	thickness	width	diameter eye outside	weight each
t	inch	inch	inch	inch	inch	inch	inch	lbs
1.25	3 ³ / ₁₆	³ / ₄	¹⁵ / ₁₆	²⁵ / ₃₂	⁵ / ₈	³ / ₄	1 ¹ / ₂	0.66
1.6	3 ¹⁹ / ₃₂	⁷ / ₈	1 ¹ / ₃₂	⁷ / ₈	²³ / ₃₂	⁷ / ₈	1 ²⁵ / ₃₂	0.97
2.5	4 ¹ / ₈	1 ³ / ₃₂	1 ⁹ / ₃₂	1 ³ / ₃₂	²⁵ / ₃₂	1 ³ / ₃₂	2 ¹ / ₃₂	1.39
3.2	4 ⁷ / ₈	1 ⁹ / ₃₂	1 ¹¹ / ₃₂	1 ³ / ₁₆	¹⁵ / ₁₆	1 ¹ / ₄	2 ⁷ / ₁₆	2.80
5.4	5 ²⁵ / ₃₂	1 ⁹ / ₁₆	1 ³ / ₄	1 ¹ / ₂	1 ¹ / ₄	1 ⁷ / ₁₆	2 ²⁹ / ₃₂	3.88
8.2	7 ¹ / ₂	1 ³¹ / ₃₂	2 ⁵ / ₃₂	1 ²⁹ / ₃₂	1 ¹ / ₂	1 ²⁹ / ₃₂	3 ²⁵ / ₃₂	7.94
12.8	9 ³ / ₃₂	2 ¹⁷ / ₃₂	2 ¹⁷ / ₃₂	2 ³ / ₃₂	1 ²⁹ / ₃₂	2 ³ / ₈	4 ¹⁵ / ₁₆	16.98
16	10	2 ³ / ₄	2 ³ / ₄	2 ¹¹ / ₃₂	2 ⁹ / ₃₂	2 ²³ / ₃₂	5 ¹ / ₂	23.8
22	12 ⁷ / ₁₆	3 ¹⁷ / ₃₂	3 ¹⁹ / ₃₂	3 ¹ / ₃₂	2 ¹ / ₂	3 ³ / ₁₆	6 ⁵ / ₈	36.8