



WATER HOSE

Premium Heavy Duty PVC Water Discharge Hose

Application:

Agriculture
 Construction
 Industrial Project
 Mining and Dewatering

Temperature:

-5°F/+170°F (-20°C /+76°C)

Marking:

 PARAGON




Tube and Cover:

Durable PVC material with a good abrasion, chemicals and UV resistance.

Reinforcement:

High Performance reinforcement designed for higher pressure.



 PART NO.	 Inner Diameter		 Wall Thickness		 Pressure	 Weight		 Max. L
	Inch	mm	Inch	mm	Psi in 60°F	lbs./Ft	Kg/m	ft/m
BRFW-150-150-300	1½	38	0.087	2.2	150	0.23	0.34	300/91
BRFW-200-150-300	2	50.8	0.091	2.3	150	0.32	0.48	300/91
BRFW-250-150-300	2½	63.5	0.095	2.4	150	0.41	0.61	300/91
BRFW-300-150-300	3	76.2	0.098	2.5	150	0.52	0.77	300/91
BRFW-400-125-300	4	101.6	0.110	2.8	125	0.76	1.13	300/91
BRFW-600-115-300	6	152.4	0.118	3.0	115	1.21	1.80	300/91
BRFW-800-70-300	8	203.2	0.122	3.1	70	1.62	2.41	300/91
BRFW-1000-65-300	10	254	0.122	3.1	65	1.95	2.90	300/91