

 **HOT WATER HOSE**
Super-Hot Water Washdown Hose

Application:

Mandrel built delivery hose suitable for hot water for cleaning service in food industry. Comply with FDA standards, free from *phthalates*.

Tube:

White smooth synthetic rubber, food quality, resistant to heat. Compliance with FDA standards.

Reinforcement:

High tensile textile plies.

Cover:

White, smooth rubber, resistant to abrasion, heat, traces of oil and weather condition. Fabric impression.

Working Pressure:

300 PSI, 20 bar

Nominal Burst Pressure:

900 PSI, 60 bar

Temperature:

-31°F/+320°F (-35°C /+160°C)

Marking:





Swivel SS316 End With Crimp ferrule



 PART NO.	 Inner Diameter		 Outside Diameter		 Weight		 Max. L
	Inch	mm	Inch	mm	lbs./Ft	Kg/m	ft/m
HWWU-050-300	1/2	13	0.90	23	0.255	0.38	200/61
HWWU-0625-300	5/8	16	1.02	26	0.295	0.44	200/61
HWWU-075-300	3/4	19	1.18	30	0.38	0.57	200/61
HWWU-100-300	1	25	1.41	38	0.53	0.79	200/61
HWWU-125-300	1¼	32	1.69	46	0.75	1.12	200/61
HWWU-150-300	1½	38	1.99	54	0.96	1.43	200/61
HWWU-200-300	2	51	2.24	68	1.38	2.05	200/61
HWWU-250-300	2½	63	2.56	81	1.73	2.58	200/61

