



WATER HOSE

EPDM Water Suction & Discharge Hose

Application:

Heavy duty EPDM liquid suction hose for industrial and agricultural water, cesspool cleaning, slurry and sludge handling, light chemical, dry material and marine use.

Temperature:

-40°F/+176°F (-40°C /+80°C)

Marking:

 PARAGON

Tube:

Black smooth EPDM rubber.

Reinforcement:

High polymerization helix.

Cover:

Green corrugated helix.



PART NO.	ID		OD		W.P.	Vacuum	Min. b. r.	Weight		Max. L
	Inch	mm	Inch	mm	Psi	In. hg	Inch	lbs./FT	Kg/m	ft/m
PE300-100	1	25	1.38	35	60	29.8	2	0.23	0.34	100/30
PE300-125	1 ¼	32	1.62	41.1	60	29.8	3.3	0.34	0.50	100/30
PE300-150	1 ½	38	1.93	49	60	29.8	3.3	0.40	0.59	100/30
PE300-200	2	51	2.5	63.5	60	29.8	5.2	0.66	0.98	100/30
PE300-250	2 ½	63	3.1	78.7	50	29.8	5.5	0.93	1.38	100/30
PE300-300	3	76	3.55	90.1	44	29.8	7.1	1.11	1.65	100/30
PE300-400	4	102	4.6	116.8	38	29.8	11.0	1.85	2.75	100/30
PE300-500	5	127	5.75	146	28	28.0	16.5	2.15	3.19	100/30
PE300-600	6	152	6.8	172.7	23	28.0	20	3.07	4.56	100/30