



PETROLEUM HOSE

Corrugated Tank Truck Oil Suction & Discharge Hose

Application:

Corrugated suction and discharge hose designed for transfer of petroleum and fuel from tank-to-tank trucks and vice versa in fuel stations. It is light weight, easy to handle and flexible hose.

Tube:

Black smooth rubber suitable for mineral oil and all grades of petroleum products with up to 50% aromatic content and unleaded petrol with maximum 5% MTBE and 15% oxygenated compounds.

Reinforcement:

High tensile textile plies, helix wire embedded and antistatic wire.

Cover:

Black, corrugated surface, conductive, resistant to abrasion, oil, fuel, ozone and weather conditions.

Working Pressure:

150 PSI, 10 bar

Nominal Burst Pressure:

450 PSI, 30 bar








Temperature:

-22°F/+194°F (-30°C /+90°C)

Marking:

iPARAGON



 PART NO.	 ID		 OD		 Vacuum	 Min. b. r.	 Weight		 Max. L
	Inch	mm	Inch	mm	In. hg	Inch	lbs./ft	Kg/m	ft /m
TTCH-100-150	1	25	1.41	36	24	2	0.47	0.70	200/61
TTCH-125-150	1¼	32	1.69	43	24	2.5	0.50	0.75	200/61
TTCH-150-150	1½	38	1.99	51	24	3.5	0.67	1.00	200/61
TTCH-200-150	2	51	2.56	65	24	5	0.94	1.40	200/61
TTCH-250-150	2½	63	3.11	79	24	6	1.28	1.90	200/61
TTCH-300-150	3	76	3.62	92	24	8	1.61	2.40	200/61
TTCH-400-150	4	102	4.72	120	24	10	2.49	3.70	200/61
TTCH-500-150	5	127	6.98	179	24	14	3.02	4.50	100/30.5
TTCH-600-150	6	152	9.25	235	24	16	4.44	6.60	100/30.5