



CONCRETE HOSE PRE-ASSEMBLED

Boom Placing Steel Wire Hose

Application:

Mandrel built steel wire reinforced concrete placement hose for concrete pumping. Available on standard and custom lengths, assembled with heavy duty and metric full flow Victaulic fittings at 62/64 HRC.

Tube:

High abrasion resistant conductive black rubber NBR.

Reinforcement:

High strength brass coated spiral steel wires.

Cover:

Weather, ozone, and abrasion resistant. Black SBR/EPDM rubber.

Working Pressure:

1233 PSI, 85 bar

Nominal Burst Pressure:

2466 PSI, 170 bar

Temperature:

-40°F/+158°F (-40°C /+70°C)

Marking:

iPARAGON



PART NO.	Inner Diameter		Outside Diameter		Length		End Type
	Inch	mm	Inch	mm	FT		
CPSH-200-1233-LL-HD2	2	51	2.75	70	25'	50'	HD ends
CPSH-250-1233-LL-HD2	2 ½	63	3.46	88	10'	25'	HD ends
CPSH-300-1233-LL-HD2	3	76	4.0	102	10'	25'	HD ends
CPSH-400-1233-LL-HD2	4	102	5.04	128	10'		HD ends
CPSH-500-1233-LL-MT2	5	127	6.10	155	4', 5', 6', 8', 10', 13'		Metric

****Custom length assembly is available for all sizes****