

WATER HOSE Premium PVC/NITRILE Discharge Hose

Application:

- | | |
|-----------------------|--------------------------|
| Agriculture | Irrigation |
| Construction | Limited oil and chemical |
| Industrial wash-down | Water pump discharge |
| Mining and dewatering | Cable covering |

Temperature:

-20°F/+176°F (-29°C /+80°C)

Marking:









Tube and Cover:

Black PVC/Nitrile material extruded in one stage.

Reinforcement:

High tensile polyester yarn reinforcement.



 PART NO.	 Inner Diameter		 Wall Thickness		 Pressure	 Weight		 Max. L
	Inch	mm	Inch	mm	Psi in 60°F	lbs./Ft	Kg/m	ft/m
BKFW-150-300-200	1½	38	0.07	1.8	300	0.20	0.30	200/61
BKFW-200-220-200	2	51	0.07	1.8	220	0.27	0.40	200/61
BKFW-250-200-200	2½	63	0.09	2.3	200	0.38	0.57	200/61
BKFW-300-175-200	3	76	0.09	2.3	175	0.48	0.71	200/61
BKFW-400-150-200	4	102	0.09	2.3	150	0.71	1.06	200/61
BKFW-600-150-200	6	152	0.12	3.0	150	1.08	1.61	200/61

Longer length available on request.