



## AIR HOSE

### Yellow Lay flat Air Hose

#### Application:

Agriculture Irrigation  
Cable covering  
Drainage, watering  
Mining and dewatering

Air Compressors  
Dry material discharge  
High pressure liquid pumping  
Flotation booms

#### Working Pressure:

Varies by sizes from 300 to 85 PSI.

#### Nominal Burst Pressure:

Safety factor 3:1

#### Tube:

Yellow PVC/Nitrile material with a good abrasion, chemical and UV resistance.

#### Temperature:

-20°F/+176°F (-29°C /+80°C)

#### Reinforcement:


High tensile polyester yarn, weave pattern to avoid kinking and snaking.

#### Marking:

 PARAGON

#### Cover:

Yellow



PART NO.	ID		OD		Pressure		Weight		Max. L ft/m
	Inch	mm	Inch	mm	working Psi	Burst Psi	lbs./Ft	Kg/m	
YFAH-075-300 *	¾	19	0.08	2.0	300	900	0.23	0.34	300/100
YFAH-100-300 *	1	25	0.08	2.0	300	900	0.32	0.48	300/100
YFAH-150-225 *	1½	38	0.11	2.8	255	765	0.41	0.61	300/100
YFAH-200-200 *	2	51	0.12	3.0	200	600	0.52	0.77	300/100
YFAH-300-150	3	76	0.12	3.0	150	450	0.76	1.13	300/100
YFAH-400-150	4	102	0.12	3.0	150	450	1.21	1.80	300/100
YFAH-600-85	6	152	0.16	4.1	85	255	1.62	2.41	300/100

\*Longer length available on request

Available with universal coupling on request.

