

# AIR HOSE



|             |  |
|-------------|--|
| <b>4121</b> | <b>JACKHAMMER HOSE ASSEMBLY - YELLOW</b> |
| <b>4122</b> | <b>JACKHAMMER HOSE ASSEMBLY - RED</b>    |



**CONSTRUCTION:** Tube is an SBR/NBR blend. Cover is EPDM, yellow or red. Reinforcement is a two-spiral polyester yarn. Crimped coupling with universal end.

**TEMPERATURE:** -22°F (-30°C) to +176°F (+80°C)

**BRANDING:** ID 4121 or 4122 300 PSI WP Production Date.

**APPLICATION:** For jackhammer applications.

**FEATURES:**

- Coupling crimped:
  - Better hose/coupling retention
  - No snagging
  - No leaking
- Easy to handle.
- Weather, heat and ozone resistant.
- Excellent abrasion resistance.
- Hose WP is 300 PSI.

| Part Number                    | I.D. |       | O.D. |       | Rein. Spirals | Max W.P. @68°F** |       | Vacuum @68°F | Weight  |      | MBR* |        | Std. Lgth. (ft) |
|--------------------------------|------|-------|------|-------|---------------|------------------|-------|--------------|---------|------|------|--------|-----------------|
|                                | in.  | mm.   | in.  | mm.   |               | PSI              | BAR   |              | lb./ft. | KG/m | in.  | mm     |                 |
| <b>YELLOW</b><br>4121-0075-050 | 3/4  | 19.05 | 1.16 | 29.50 | 2             | 150              | 10.35 | n/a          | 0.54    | 0.80 | 5.00 | 127.00 | 50              |
| <b>RED</b><br>4122-0075-050    | 3/4  | 19.05 | 1.16 | 29.50 | 2             | 150              | 10.35 | n/a          | 0.54    | 0.80 | 5.00 | 127.00 | 50              |

**\*\*Assembly working pressure. Hose WP is 300 PSI**

Safety clip and lanyard not supplied. For safety reasons, please follow all OSHA regulations.

**\*MBR = Minimum Bend Radius**

**Working pressure is temperature dependent. See page 5 for more information.**

**All sizes may not be stocked in all locations. Check with customer service for availability.**

**We disclaim any liability for use of our products in applications other than which they are designed.**